## RESIDENTIAL RIBLINE® ROOFING UNDER RIDGE / APRON CHIMNEY FLASHING

RIDGE / APRON HFM SEAL AND FASTEN SCREW TO PURIN BACK FLASHING NOTCHED TURN DOWN OR SOFT EDGE OVER RIBLINE. GAP 2-5MM CLEAR OF TROUGH ROOFING ROOFING INDUSTRIES 'RIBLINE' FLASHING SOFT EDGE DRESSED INTO PROFILE LAYING SEQUENCE: A. SOFTEDGE APRON. B. SIDE FLASHING. C. BACK FLASHING. D. COVER FLASHING (CHASED)

## Detail Number: RI-RRROIGA

Date drawn: 07/07/2017

## NOTES:

- I. SITUATION I: IN LOW, MEDIUM OR HIGH WIND ZONES, WHERE ROOF PITCH IS 10° OR GREATER.
- 2. SITUATION 2: FOR ALL ROOF PITCHES IN VERY HIGH # EXTRA HIGH WIND ZONES, FOR ALL LESSOR WIND ZONES WHERE ROOF PITCH LESS THAN LO®
- 3. ALSO REFER TO NZ METAL ROOF & CLADDING CODE OF PRACTICE.

CATCHMENT	MAX ROOF LENGTH	
WIDTH	ABOVE PENETRATION	
0-400	18 METRES	
400-600	I 6 METRES	
600-800	I 2 METRES	
800-1200	8 METRES	

SITE WIND ZONE	MIN mm (cover)	
(As per NZS3604)	X	Y
SITUATION I (1)	150	2 CRESTS
SITUATION 2 (2)	200	2 CRESTS

## NOTES:

- These details are generally in compliance with E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

  Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

  Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and In some cases specific details by 'Roofing Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and In some cases specific details by 'Roofing Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof \$ Wall Cladding Code of Practice and Industries'

  These details are generally in compliance with E2/AS I and 'Roof E2/AS I and 'Ro
- The building designer is ultimatley responsible to ensure that details used meet the requirements of the NZ Building Code for the specific project.
- Details of the supporting structure including cavity battens are indicative only and are the responsibility of the building designer. For steel framed buildings thermal break cavity battens may be required.
- Underlay selection and building wrap types are the responsibility of the designer, Netting or other support is generally required at roof pitches less than 8 degrees combined with a self supporting paper. At roof pitches of 8° and above where non-self supporting paper is used or purlin spacing is in excess of self supporting criteria, netting or other support should be used. Alternative support to netting should be used in severe coastal environments including when aluminium is used.
- These details are for Roofing Industries profile/s as nominated and may not be applicable to other profiles.
- This drawing is the copyright of 'Roofing Industries' and can only be copied or reproduced with their permission.
- These details to be read with Roofing Industries profile technical summary regarding wind loads and fixings.
- Further information can be obtained from the NZ Metal Roof \$ Wall Cladding Code of Practice: www.metalroofing.org.nz OR NZBC clause E2/AS I.

Copyright detail (C) 2

