



Product Specification

Product Name:

PORTER'S PALM BEACH BLACK

PRODUCT DESCRIPTION:

Porter's Palm Beach Black is a water-based, colourfast black stain for all timber types. Depending on application method used, Palm Beach Wash will produce a transparent effect to enhance the grain of timber, or a saturated, opaque effect. Made with highest quality UV resistant exterior grade pigments, Palm Beach Black delivers excellent water resistance and UV protection. The protective black pigments used in Palm Beach Wash have a reflective quality that when observed closely will resemble the satin-like gleam evident charcoal.

LOCATION:

Interior and exterior.

ENVIRONMENTAL INFORMATION:

This product contains: 42.6g/L VOC's (Volatile Organic Compounds contribute to atmospheric pollution.

APAS* Target level for this product: 70g/L.

Although this product is unique and there is no comparative product type, the closest comparison would be a typical water-based flat exterior paint that has a VOC level of approx. 70g/L

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

The following descriptors have been adopted by

APAS:

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

* Australian Paint Approval Scheme.

SUGGESTED APPLICATIONS:

Excellent for use on garden furniture, exterior plywood, weatherboard, shingle or interior furniture and floorboards.

COLOUR:

Translucent black.

LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C.

Not suitable for decking.

PREPARATION:

The substrate should be sanded to expose clean bare timber free from paint, grease, oil, mould and previous coatings. Timber should be dry and free of contaminants. On previously painted surfaces *all* paint must be removed and surface stripped bare and thoroughly sanded before application.

When using Palm Beach Black over timbers that are oily in nature, such as brush box, blackbutt, jarrah, spotted gum, teak and other hardwoods that have a natural oiliness or waxiness (often used for decks for this reason) allow the timber to weather for at least 3 months to dry out the surface to allow the Palm Beach Black to penetrate, otherwise the natural oils in the timber will repel the water-based Palm Beach Black causing lack of adhesion, resulting in peeling and delamination.

APPLICATION:

Stir thoroughly prior to use.

FOR A TRANSLUCENT EFFECT:

Apply 1 coat by brush, roller or spray, following the grain and ensuring even coverage. No longer than 3 minutes after application, wipe off excess

paint with a soft, absorbent cloth so that the crevices and grain of the timber hold the colour. If required apply a second coat to deepen the colour, using the same method. Touch dry 30 minutes (using this method). Allow 4 hours dry time before applying second coat. Allow to dry 24 hours.

FOR AN OPAQUE EFFECT:

Apply 1 coat by brush, roller or spray, following the grain and ensuring even coverage. Touch dry 1 hour (this method only). If required apply a second coat to deepen the colour. Allow 4 hours dry time before applying second coat. Allow to dry 24 hours.

Application tip – can be diluted with water (up to 20%) for a lighter/weaker effect.

COVERAGE RATES:

Covers up to 20m² per litre, depending upon porosity, surface texture and wastage rates. Please note that on weathered or aged timber with an open grain or more absorbent surface, coverage may be decreased.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

Porter's Palm Beach Black can be sealed and protected with Porter's Clearcote (coverage 15m² per litre). Allow Palm Beach Black to dry for 72 hours before applying Clearcote. Test before use as a slight colour variation may occur.

PACKAGING:

Porter's Palm Beach Black is available in 1 litre & 4 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints
288 Coward St
Mascot NSW 2020
Australia
Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
E-mail: enquiries@porters.com.au
Web: www.porterspains.com

Porter's Paints
150 Hutt Park Rd
Gracefield
Lower Hutt 5010
New Zealand
Ph: 0800 672 468