

PRODUCT OVERVIEW 260 TRANSLUCENT ROOF



260 TRANSLUCENT OPENING ROOF

## 260 TRANSLUCENT ROOF

let there be light

If loss of light is an issue when the Opening Roof is closed then the unique 260 Translucent Opening Roof provides the answer:

This roof now features an all new white in-fill panel of Acrylic Naturelite Plexiglas ®.

Plexiglas offers natural UV protection throughout the material – it does not rely on an applied surface coating for UV protection. It is one of the reasons Plexiglas is used in aircraft cabin windows to protect from strong UV light and substantial differences in pressure and extreme cold.

This same material is now used on all 260 Translucent Opening Roofs – high light transmission coupled with naturally UV-stable technology is as good as it gets.

This style of opening roof now comes with a 185mm extra wide gutter to all four sides as standard.

### OPERATING YOUR OPENING ROOF - THE CHOICE IS YOURS

All motors, sensors and controllers carry a 5 year warranty. Refer to the Louvretec Product Warranty for details.



Remote controlled

Wall switches

Home Automation

Sensors

Hand operated



HAND HELD AND WALL MOUNTED REMOTES




STANDARD WALL MOUNTED SINGLE/MULTI OPTIONS



myLink™



RAIN SENSOR



LOUVRETEC GEARBOX

### OPTIONAL EXTRAS

Enhance your site to suit your needs.



OPTIONS IN GUTTERS, BLADES, BEAMS, POSTS.



FREESTANDING OR INTEGRATED.

### SURFACE COATINGS

A wide range of options are available.



ANODISED



WOOD FINISH



POWDERCOATED