

PRODUCT OVERVIEW LOUVRETEC OUTDOOR BLINDS GENERAL AND MAINTENANCE

CARE & MAINTENANCE

In order to prolong the life of your Louvretec Outdoor Blind and provide ongoing optimum performance, we recommend the following:

- Regular cleaning (at least every 3 months)
- Just like your car, Louvretec Outdoor Blinds do require regular cleaning.
- Ensure surfaces are free from dirt, dust and grime.
- Clean Louvretec blind with a soft brush.
- Run a soft brush alongside channel to prevent dirt and dust build up
- Clean the blind and aluminium with a soft cloth and warm soapy water, or a small amount of detergent if required.
- Lightly rinse, do not use a high pressure hose, or bore water to clean the blind.
- For the Louvretec Ziptrack system, in dusty or seafront locations it is recommended once a year to add lubricant to assist the ongoing smooth operating of the blind. This MUST BE a silicone spray, such as food grade Helmar H4000 or CRC808. To apply the lubricant, lower your blind all the way down, and apply the silicone spray to the front of the blind in the groove between the spline and the track. After application, open and close the blind several times to help evenly distribute the silicone.

care of your blind

- Once a week fully extend your blind to even out the fabric and let it breathe. Leave it down all day to let it retain its shape.
- Regularly operate your blind – at least once a week
- Sagging as a result of the blinds own weight will occur. This is not a fault in the system and is unavoidable.
- Minor variances will occur with your blind, such as the bottom bar hanging down slightly more or less from one side. This is normal.

common characteristics

- Depending on fabric selection, when the Louvretec blind is initially pulled down some ripples may be evident.
- The ripples will lessen over time as the weight of the blind will stretch the fabric slightly,
- When a motorised blind is operated some “jolting” may be evident, this occurrence does not damage the blind.
- Depending on the blind width, the mesh or PVC often require joining seams. These may run either vertically or horizontally and may have two or three joins in one blind.

