

# MANUAL

## MASONS ENVIRO AAC ON 45mm CAVITY [ Timber Framing ]

### DISCLOSURE NOTE:

The information provided is for guide only and must be used along side professional architectural/structural design. Professional architectural/structural design takes preference with any conflicting areas of the building design. All documents or data downloaded from [www.mpb.co.nz](http://www.mpb.co.nz) or emailed from MASONS Plastabrick Limited is the intellectual property of MASONS Plastabrick Limited. MASONS Plastabrick Limited takes no responsibility for any of the documents or data being used for any other purpose than for professional architectural/structural design.

## TABLE OF CONTENTS

Description	Page #
AAC ENVIRO Panel Technical Information	4-6
AAC ENVIRO Panel List of Components	7-8
Appraisal Design Information	9-11
Construction Details	12-60
Pre-cladding Checklist	61-62
Pre-coating Checklist	63
Final Checklist	64

Detail #	Description	
01	AAC ENVIRO Tie	12
	General Layout Concrete Floor	
02	- with rebate	13
03	- without rebate	14
04	General Layout Timber Floor	15
05	Typical AAC ENVIRO Tie and Panel Layout	16
06	Typical Wall Cross Section	17
	Concrete Footing	
07	- with rebate 3D view	18
08	- with rebate section view	18
09	- without rebate 3D view	19
10	- without rebate section view	19
	Timber Floor Footing	
11	- 3D view	20
12	- section view	20
	Internal Corner	
13	- section view	21
14	- 3D view	21
	External Corner	
15	- section view	22
16	- 3D view	22
	Control Joints	
17	- Vertical Plan View	23
18	- Horizontal Section View	23

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME

Detail #	Description	Page #
	<b>Opening Flashings</b>	
19	- window head section view	24
20	- window head 3D	24
21	- window sill	25
22	- window jamb	25
23	- garage door jamb	26
24	- garage door head	26
25	- PVC corner soaker installation	27
	<b>Meterbox</b>	
26	- section view	28
27	- 3D view	28
28	<b>Pipe Penetration</b>	29
29	<b>Downpipe Fixing</b>	30
	<b>AAC ENVIRO Column/Post</b>	
30	- plan view	31
31	- section view	31
	<b>AAC ENVIRO/Weatherboard</b>	
32	- vertical junction	32
33	- corner junction internal	33
34	- corner junction external	33
35	- mid floor junction	34
	<b>AAC ENVIRO/Brick Veneer Junction</b>	
36	- internal corner section view	35
37	- internal corner 3D view	35
38	- external corner section view	36
39	- external corner 3D view	36
40	<b>Roof/Wall Junction</b>	37
41	<b>Soffit Junction</b>	38
	<b>Parapet Construction</b>	
42	- metal capping	39
43	- ENVIRO panel capping	40
	<b>Parapet/handrail to wall junction</b>	
44	- section view	41
45	- metal capping 3D view	42
46	- ENVIRO panel capping 3D view Step 1	43
46A	- ENVIRO panel capping 3D view Step 2	44
46B	- ENVIRO panel capping 3D view Step 3	45
46C	- ENVIRO panel capping 3D view Step 4	46

## MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME

Detail #	Description	Page #
47	Deck/Pergola Wall Fixing	47
48	Alternative Window Sill	48
49	General Layout and Airflow	49
50	Control Joint Mid-Floor	50
51	Kickout Flashing	51
52	Concrete Floor Door Sill	52
53	- with rebate	53
54	- without rebate	54
55	Timber Floor Door Sill	55
56	Door Sill Flashing 3D view	56
57	Upper Raking Soffit	57
58	- metal flashing	58
59	- hidden flashing	59
60	Window Head - Monotek	60
61	AAC Panel / Monotek junction	61
62	Opening Flashing - Window Sill Option 1	62
63	Soffit Edge	63

## AAC ENVIRO PANEL VENEER TECHNICAL INFORMATION

### Scope and Limitations:

The ENVIRO AAC panel System is to be installed on timber framed buildings within the scope of paragraph 1.2 of acceptable solution E2/AS1 that are designed to NZS 3604 or steel framed buildings that are designed to NASH 3405.

### General Description:

50mm Autoclaved Aerated Concrete (AAC) masonry panels with corrosion protected vertical & horizontal steel reinforcing suitable for exterior cladding of residential & light commercial buildings. AAC panels are coated with MASONS AAC reinforced plastering system to produce the clients finishing requirements once fixed in place. AAC ENVIRO Panels are a proven masonry material to be used with lightweight timber or steel framing. The panels come in a standard 2200mmx600mmx50mm size sheet.

## MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## AAC ENVIRO PANEL VENEER TECHNICAL INFORMATION CONTINUED

- Reference Document: CodeMark Assessment Brief # CMA-AM 130241  
Issued by CertMark Australia PTY Ltd.



### CONSIDERATIONS

#### General:

AAC ENVIRO Panels must be installed as per the details shown in this manual to ensure the quality of the cladding system. AAC ENVIRO Panels must not be installed in any situation where it will come into contact with the ground. AAC ENVIRO Panels can not be used as retaining walls.

Pre-Installation checks and installation guide can be found on page 7 of the CodeMark Assessment Brief # CMA-AB 130241.

#### Safety Precautions:

AAC ENVIRO Panel is Autoclaved Aerated Concrete. As with all concrete and fibre cement products, the dust produced when cutting or grinding them contains crystalline silica. This dust is irritating to the eyes, skin and respiratory system. Inhalation of this dust can cause irreversible damage to health. Wear suitable protective clothing and gloves at all times. When cutting, drilling or grinding panels do so in an open air environment or areas that are well ventilated and wear approved safety glasses and dust mask. All aspects of cutting, drilling or grinding must comply with the latest regulations of the Occupational Safety and Health division of the Labour Department.

#### Handling & Storage:

AAC ENVIRO Panels should be stored on site on the pallets they were delivered on and kept covered and free of dampness until required. Care should be taken when handling to limit damage to edges or corners.

#### AAC ENVIRO Panel Properties:

Dry Density:	525kg/m <sup>3</sup>
Intensity:	4.0Mpa
Dry Shrinkage Value:	0.8mm/m
Water Absorption (by volume):	up to 24 - 35%
Thermal Conductivity:	0.13w/mk
Sound Transmission Class (STC):	33 (50mm bare panel)
Fire Resistance:	1.5 hours

#### Performance:

AAC ENVIRO Panels fixed in accordance with the instructions & details in this manual will meet the requirements & relevant sections of the New Zealand Building Code including:

- B1 - Structure
- B2 - Durability
- E2 - Moisture
- F2 - Hazardous Building Materials.

#### Structure:

In terms of NZS 3604:2011 incorporating amendments 1 & 2, AAC Panels fixed as per this manual are able to withstand all earthquake & wind loadings in all areas of New Zealand.

## MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME

### **Durability & External Moisture:**

AAC ENVIRO Panel fixings in accordance with this manual will meet the requirements of NZBC Clause B2.3.1 (b). The cavity is provided to;

- Allow moisture to run down the inside of the AAC ENVIRO Panel and escape through the weepholes without bridging the cavity.
- Provide sufficient air space permitting air to circulate within the cavity and dry the AAC ENVIRO panel.

The MASONS plastering system meets the requirements of NZBC Clause B2.3.1 & E2.2.3 to finalise this wall cladding system.

### **Hazardous Building Materials:**

AAC ENVIRO Panels are non-hazardous in terms of Clause F2 of the NZBC provided the safety precautions included in this manual are adhered to.


### **Mass:**

AAC ENVIRO Panel is within the range of light to medium weight wall cladding as defined in NZS 3604:2011. The dry mass of AAC ENVIRO Panel is 25kg/m<sup>2</sup> (33kg per 2200x600 panel) The coating system selected will determine if the cladding exceeds the light wall cladding and which weight range in relation to NZS 3604:2011 the cladding finishes within.

### **Insulation:**

Insulation is installed as required by NZBC E3/AS1 Clause 1.1.1(a)

## LIST OF COMPONENTS



**PANELS:**

2200mmx600mmx50mm size sheet. 50mm Autoclaved aerated concrete (AAC) panels. AAC ENVIRO Tie, 45x45 H3.2 timber batten cut to 200mm lengths, see detail 01.

**NAILS:**

90mm galvanised ring shank nails are used to fix the ENVIRO ties to the framing. All nails shall comply with compliance document E2 / AS1 Table 20.

### PLASTER SYSTEM:

**MASONS Plastabrick AAC coating system is used over ENVIRO panels. MASONS reinforcing mesh. MASONS pre-meshed corner beads.**

## MORTAR GLUE:

**ENVIRO jointing glue supplied by MASONS for use in jointing and stopping of ENVIRO Panels.**

## MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME

**SCREWS:**

14x75mm class 3 bugle head screws (14x75 bugle head stainless steel screws in sea spray zones) are used for fixing the 50mm panels to the ENVIRO ties. All screws shall comply with Compliance Document E2 / AS1 Table 20.

**FLASHINGS & MOULDINGS:**

MASONS PVC reveal bead flashing  
MASONS PVC sill flashing  
Powder coated aluminium head flashing  
MASONS PVC base shoe and cavity closure  
MASONS PVC vented cavity closure  
MASONS PVC corner soaker

**ADHESIVE:**

All PVC flashing's and mouldings are glued to the ENVIRO panel using BOSTIK safe seal construction adhesive.

**DAMP PROOF COURSING (DPC):**

MASONS DRYFIX DPC supplied by MASONS.

**TAPE:**

EIFS tape or NZ Tape Specialists future seal tape MASONS Barricade Plus Window Tape.

**SEALANTS:**

Low expandable PU foam that complies with AAMA 812-04 for use in control joints of ENVIRO panels  
BOSTIK safe seal paintable urethane sealant should be applied in strict accordance with the manufacturers specifications.

**ANTI-CORROSION PAINT:**

CRC Zinc it (aerosol can 350g) or similar complying with AS/NZS 2311:2000, Part 2.3 Is applied to all exposed reinforcing steel.

**VENTS:**

50x100mm aluminium vents manufactured by MASONS.

## APPRAISAL NOTE:

## DESIGN INFORMATION:

### Framing

#### Timber Framing

7.1 Timber used in timber framing shall be treated as required by NZS 3602.

7.2 Timber framing must comply with NZS 3604 for both buildings or parts of buildings within the scope limitations of NZS 3604. Where buildings or parts of buildings are outside the scope of NZS3604 then they must be to specific design in accordance with NZS 3603 and AS/NZS 1170. Where specific design is required, the framing must be of at least the equivalent stiffness to the framing provisions of NZS 3604. In all cases, studs must be at a maximum of 600mm centres.

7.3 Timber framing and AAC ENVIRO® Tie battens must have a maximum moisture content of 18% at the time of cladding application. (Problems could arise later on due to timber shrinkage if over 18%) Steel Framing

#### Steel Framing

7.4 Steel framing must be to a specific design meeting the requirements of the NZBC. (NASH 3405: 2006)

7.5 The minimum steel framing specification is 'C' section studs and nogs of overall section dimensions of 76mm web by 40mm flange. Steel thickness must be a minimum 0.55mm.

7.6 For steel framed buildings situated within NZS3604 defined wind zones up to and including 'Very High' studs, must be at maximum 600mm centres. All other buildings studs must be at maximum 400mm centres. Dwargs must be fitted flush with the stud.

For latest steel framing information refer to <http://www.nash.asn.au/nash/>

#### ENVIRO® AAC Panel Layout

7.7 ENVIRO® AAC Panels are installed horizontally in a stretcher bond pattern. Vertical panel edges may be jointed on stud or off stud. ENVIRO® AAC Panels must be supported at fixing locations with vertical cavity battens or cavity spacers 100mm long max. in accordance with the requirements of NZBC acceptable Solution E2/AS1, paragraph 9.1.8.2(f). At the base of the wall the ENVIRO® AAC Panel can be either rested on a concrete rebate (100mm below finished floor level) or hung 50mm below the finished floor level.

### General

8.1 Punchings in the cavity closer and head flashing provide a minimum ventilation opening area of 1000mm<sup>2</sup> per lineal metre of wall as per the requirements of NZBC acceptable Solution E2/AS1, paragraph 9.1.8.3 (b).

8.2 The MASONS Plastabrick aluminium weep hole vents provide a minimum ventilation opening area of 1000mm<sup>2</sup> per lineal metre of wall when fixed at 1200mm centres as per the requirements of NZBC acceptable Solution E2/AS1 paragraph 9.1.8.3 (b).

8.3 The clearance between the finished floor level and ground level as outlined in NZS 3604 must be adhered to at all times. At ground level, paved surfaces must be kept clear from the bottom edge of the ENVIRO® AAC Panel System by a minimum of 100mm, and unpaved surfaces by 175mm in accordance with the requirements of NZBC acceptable Solutions E2/AS1, Table 18.

8.4 At balcony, deck or roof to wall junctions, the bottom edge of the ENVIRO® AAC Panel must be kept clear of any adjacent surface, or above the top surface of any adjacent roof flashing by a minimum of 35mm in accordance with the requirements of NZBC acceptable Solution E2/AS1, paragraph 9.1.3.6.

8.5 Where the ENVIRO® AAC Panel Systems abuts other cladding systems, designers must detail the junction to meet their own requirements whilst meeting performance requirements of the NZBC. The Technical Literature does provide some guidance. Details not included within the Technical Literature have not been assessed and are therefore outside the scope of this Appraisal.

## MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME

## Control Joints

9.1 Control joints where ENVIRO® AAC Panels are used must be constructed in accordance with the Technical Literature and provided as follows;

- Horizontal control joints - To be installed when intermediate floor joists are not seasoned and/or when the height of the wall exceeds 10m
- Vertical Control Joints - at maximum 10m centres; aligned with any control joint within the structural framing, or where the system abuts other cladding systems. Located at both internal and external corners.

(Note: Where possible control joints shall be located in line with window and door openings. Horizontal and vertical control joints must be located over structural supports. The Technical Literature provides some guidance for the design of vertical control joints where the system abuts different cladding types. Details not included within the Technical literature or those that are marked as 'Specific Design Only' are outside the scope of the Appraisal Certificate and are the responsibility of the designer.)

## Interstorey Junction

10.1 Inter-storey drained joints must be provided for walls over 2 storeys in height, in accordance with the requirements of NZBC acceptable solution E2/AS1, paragraph 9.1.9.4 (b).

## Structure — Clause B1

### Mass

11.1 The mass of ENVIRO® AAC Panel is approximately 25kg/m<sup>2</sup> and when the MASONS Plaster System is applied, the wall cladding is then considered a medium wall cladding in terms of NZS 3604.

### Impact Resistance

11.2 The system has adequate resistance to impact loads that the cladding system is likely to be subjected to when used in a residential situation. The likelihood of impact damage to the system when used in light commercial situations should be considered at the design stage, with appropriate protection provided such as bollards or barriers where necessary.

### Wind zone

11.3 The ENVIRO® AAC Panel system is suitable for use in all building wind zones as per NZS 3604, up to, and including 'Very High' where buildings are designed to meet the performance requirements of NZBC acceptable solution E2/AS1, or up to the ultimate limit state (ULS) wind pressure of 2500Pa when the building is subject to specific design.

## ENVIRO® AAC Panel fixing

11.4 Where a 45mm cavity is produced the ENVIRO® Tie Batten is fixed through to the wall framing at 500 centres vertically. The ENVIRO® AAC Panel must then be fixed through into the ENVIRO® Tie Batten and cavity spacers at 500mm vertical fixing centres.

11.5 Where a 20mm cavity is produced the ENVIRO® AAC Panel must be fixed through the cavity battens and cavity spacers to the wall framing at maximum centres of 500mm

Note:

- 500mm centres is applicable to both Low – very high NZS 3604 defined building wind zones with studs at maximum 600mm centres, and; Specifically designed buildings up to design differential 2.5kPa ULS wind pressure with studs at maximum 600mm centres.
- Fixings to be positioned minimum 50mm in from the edge of the panel giving an overall layout of 500mm centres per panel.
- Fixings are also required horizontally at 600mm centres.
- A minimum of 6 bugle head screws per panel is required
- Bugle head screws must be embedded a maximum 10mm into the ENVIRO® AAC Panel.

## Durability — Clause B2

12.1 The ENVIRO® AAC Panel System when used in accordance with this Appraisal Certificate and subjected to normal conditions of environment and use will meet the performance requirements of NZBC B2.3.1 (b), 15 years for the cladding system and plaster finish, and the performance requirements of NZBC B2.3.1 (c), 5 years for the exterior paint system (the life of the product not being less than 5 years).

# MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## Maintenance

12.2 Regular maintenance is essential to ensure the performance requirements of the NZBC are met and to ensure the maximum serviceability of the ENVIRO® AAC Panel System.

12.3 Regular cleaning (at least annually) of the paint coating is required to remove grime, dirt and organic growth as per the Technical Literature in order to maximize the life and appearance of the acrylic paint coating. Paint coatings must be reapplied every 5 years in accordance with the paint manufacturers instructions. Re-coating colours shall have an LRV (light reflectance value) of 40% or greater.

12.4 Regular inspections (at least annually) must be made on the system to ensure that all aspects of the ENVIRO® AAC Panel System including the coating system, plasters, flashings and any sealed joints remain in a weatherproof condition. Any cracks, damaged areas or areas showing signs of deterioration that could allow water ingress, must be repaired immediately. The ENVIRO® AAC Panel System must be maintained and repaired in accordance with the instructions from MASONS Plastabrick Ltd.

12.5 Minimum ground clearance as set out in this Appraisal and Technical Literature must be maintained at all times during the life of the system to maintain the durability and weathertightness of the system.

## Control of External Fire Spread

13.1 The ENVIRO® AAC Panel System is considered to meet the performance requirements of NZBC C3.3.5 for use as an external wall cladding when restricted to:

- Single storey buildings 1m or more from the boundary for all purpose groups
- Buildings up to 7m high, 1m or more from the boundary, for all purpose groups other than SC and SD.

13.2 Clearance separations from chimneys and flues are not required for the ENVIRO® AAC Panel. Where the panel is used with or attached to a heat sensitive material, the heat sensitive materials must be separated from chimneys and flues in accordance with the performance requirements of NZBC acceptable Solution C/AS1, part 9 for protection of combustible materials.

## External Moisture — Clause E2

14.1 When installed in accordance with this Appraisal Certificate and Technical Literature, the ENVIRO® AAC Panel System will prevent the penetration of water that could cause undue dampness and/or damage to building elements and will therefore comply with clause E2.3.2.

14.2 The cavity must be sealed off from the roof and subfloor space in order to meet the performance requirement of E2.3.5.

14.3 The ENVIRO® AAC Panel System allows excess moisture present at the completion of construction to be dissipated without causing permanent damage to the building elements to meet the performance requirement of Clause E2.3.6.

14.4 The details provided within the Technical Literature for weather resistance are based on the design principle of employing both a 1st and 2nd line of defence against moisture entry for joints, penetrations and junctions. Moisture ingress is prevented by detailing joinery or wall junctions as shown in the ENVIRO® AAC Panel System technical manual. Any weathertight-ness details developed by the designer are outside the scope of this Appraisal Certificate and are the responsibility of the designer.


14.5 The presence of a drained cavity does not reduce the requirement to ensure the cladding wall and all the relevant junction, penetrations etc remain weather resistant in order to comply with Clause E2.3.6.

## Water Vapour

14.6 The ENVIRO® AAC Panel System is not impermeable therefore allows the escape of water vapour.

14.7 When the ENVIRO® AAC Panel System is installed over a steel frame, an expanded polystyrene thermal break must be installed over the building wrap overeach steel member (stud, nog, top and bottom plate) to provide a thermal break in accordance with the requirements of NZBC acceptable Solution E3/AS1, Paragraph 1.1.4(d). The thermal break will also act as the cavity batten for the ENVIRO® AAC Panel System and will therefore be a minimum 20mm thick in accordance with the requirements of acceptable Solution E2/AS1, paragraph 9.1.8.4.

14.8 Where the thermal break is used across steel nogs it shall be reduced in thickness to 10mm thick to comply with the requirements of acceptable Solution E2/AS1, Paragraphs 9.1.8.2(f) and 9.1.8.3 (b).




## H3.2 AAC ENVIRO TIE

## Detail 01 NTS

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME






## GENERAL LAYOUT Concrete Floor With Rebate

## Detail 02 NTS


### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## GENERAL LAYOUT Concrete Floor Without Rebate

## Detail 03 NTS


### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## GENERAL LAYOUT Timber Floor

## Detail 04 NTS


### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## TYPICAL AAC ENVIRO TIE & PANEL LAYOUT

## Detail 05 NTS


### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## TYPICAL WALL CROSS SECTION


## Detail 06 NTS

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## CONCRETE FOOTING With Rebate - 3D View


## Detail 07 NTS




## CONCRETE FOOTING With Rebate

## Detail 08 Scale 1:10

### MASON'S ENVIRO AAC ON 45mm CAVITY TIMBER FRAME




## CONCRETE FOOTING Detail 09 NTS Without Rebate - 3D View




## CONCRETE FOOTING Detail 10 Scale 1:10 Without Rebate

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



**TIMBER FOOTING**  
**3D View**

**Detail 11 NTS**




**TIMBER FOOTING**

**Detail 12 Scale 1:10**


**MASONS ENVIRO AAC ON 45mm CAVITY**  
**TIMBER FRAME**





**INTERNAL CORNER**


**Detail 13 Scale 1:5**



**INTERNAL CORNER  
3D View**


**Detail 14 NTS**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## EXTERNAL CORNER


## Detail 15 Scale 1:5



## EXTERNAL CORNER 3D View


## Detail 16 NTS

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## CONTROL JOINTS - VERTICAL Plan View

**Detail 17 Scale 1:5**



## CONTROL JOINTS - HORIZONTAL Section View

**Detail 18 Scale 1:5**

Note: Refer to page 10 Section Control Joints Re: For the placement of control joints.

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME

MASONS Barricade PLUS Window Tape over flashing onto MASONS Barricade Building Wrap extended 20mm each side of opening

14gx75mm Bugle Head Type 17 Screws embedded 10mm max. into panel. Min 50mm from edge.

MASONS AAC render & coating system

50mm AAC ENVIRO Panel


MASONS Barricade PLUS Window Tape

Turn up ends of head flashing 20mm

Approved foam tape adhered to top of window flange

Aluminium Window Head Moulding Flashing with 15° Fall to be installed by builder

MASONS Barricade Building Wrap



## OPENING FLASHING Window Head

**Detail 19**  
**Scale 1:2**

MASONS Barricade Building Wrap

MASONS Barricade PLUS Window Tape over flashing onto MASONS Barricade Building Wrap extended 20mm each side of opening


Turn up ends of head moulding 20mm

BOSTIK Safe Seal flexible sealant

Aluminium Window Head Moulding Flashing with 15° Fall to be installed by builder

Approved foam tape adhered to top of window flange


MASONS Barricade PLUS Window Tape



## OPENING FLASHING - 3D View


**Detail 20 NTS**

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## OPENING FLASHINGS - Window Sill

## Detail 21 Scale 1:2




## OPENING FLASHINGS - Window Jamb

### MASONS ENVIRO AAC ON 45mm CAVITY


### TIMBER FRAME

## Detail 22 Scale 1:2



## OPENING FLASHING GARAGE DOOR - Jamb

**Detail 23 Scale 1:2**




## OPENING FLASHING GARAGE DOOR - Head






**Detail 24 Scale 1:2**

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME





**FRAMING**



## OPENING FLASHINGS PVC CORNER SOAKER & CORNER GUARD INSTALLATION

**Detail 25 NTS**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**

45x45 H3.2 AAC ENVIRO Tie  
kept 100mm min above wedge

MASONS Barricade Building Wrap  
H3.2 timber wedge with 15° slope  
MASONS Barricade PLUS Tape  
over wedge adhered to MASONS  
Barricade Building Wrap

MASONS Barricade PLUS  
Tape to meterbox perimeter  
adhered to MASONS  
Barricade Building Wrap

45x45 H3.2 AAC ENVIRO Tie

50mm AAC ENVIRO Panel

Blocking between studs

MASONS AAC render  
& coating system

H3.2 timber wedge with 15° slope to  
direct water to outside edge. Masons  
Barricade PLUS Tape over top adhered  
to MASONS Barricade Building Wrap

PVC reveal bead flashing adhered to  
face of meter box. BOSTIK safe seal  
over and plastered in.

Low expandable foam backing

MASONS Barricade PLUS Tape  
adhered to MASONS Barricade  
Building Wrap & meter box

PVC reveal bead flashing adhered  
to face of meter box. BOSTIK safe  
seal over and plastered in.

Low expandable foam backing

45x45 H3.2 AAC ENVIRO Tie

MASONS Barricade Building Wrap

Meter box

Not to Scale

MASONS  
Barricade  
PLUS  
Tape to  
perimeter  
of Meter  
Box

MASONS  
Barricade  
Building  
Wrap


## METER BOX Detail 27 NTS

## METER BOX

## Detail 26 Scale 1:5

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME






## PIPE PENETRATION

## Detail 28 Scale 1:2


### MASON'S ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## DOWNPIPE FIXING


**Detail 29 Scale 1:2**

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



**AAC ENVIRO  
COLUMN/POST - Plan View**


**Detail 30 Scale 1:5**



**AAC ENVIRO  
COLUMN/POST - Section View**

**Detail 31 Scale 1:5**


**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## AAC ENVIRO PANEL / WEATHER BOARD VERTICAL JUNCTION Plan View


**Detail 32 Scale 1:2**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## ENVIRO AAC PANEL / WEATHERBOARD Corner Junction Internal


**Detail 33 Scale 1:5**



## ENVIRO AAC PANEL / WEATHERBOARD Corner Junction External

**Detail 34 Scale 1:5**

### MASON'S ENVIRO AAC ON 45mm CAVITY TIMBER FRAME




## AAC ENVIRO PANEL / WEATHER BOARD - Mid Floor Junction

**Detail 35 Scale 1:5**


### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME

Note: Do not over use expanding foam. Ensure cavity is kept clear.



## AAC ENVIRO PANEL / BRICK VENEER - Internal Corner Junction


**Detail 36 Scale 1:5**



## AAC ENVIRO PANEL / BRICK VENEER Internal Corner Junction - 3D View


**Detail 37 NTS**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## AAC ENVIRO PANEL / BRICK VENEER External Corner Junction

**Detail 38 Scale 1:5**




## AAC ENVIRO PANEL / BRICK VENEER External Corner Junction - 3D View

**Detail 39 NTS**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**






## ROOF / WALL JUNCTION

## Detail 40 Scale 1:2


### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## SOFFIT JUNCTION

## Detail 41 Scale 1:10


### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## PARAPET CONSTRUCTION - Metal Capping

**Detail 42 Scale 1:5**


**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## PARAPET CONSTRUCTION - Plastered Capping

**Detail 43 Scale 1:5**


**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## PARAPET / HANDRAIL TO WALL JUNCTION With Metal Capping

**Detail 44 Scale 1:5**


**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## PARAPET / HANDRAIL TO WALL JUNCTION With Metal Capping - 3D View

## Detail 45 NTS


**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## PARAPET / HANDRAIL TO WALL JUNCTION ENVIRO Panel Capping Step 1

## Detail 46 NTS

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**




## PARAPET / HANDRAIL TO WALL JUNCTION ENVIRO Panel Capping Step 2

## Detail 46A NTS

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**






## PARAPET / HANDRAIL TO WALL JUNCTION ENVIRO Panel Capping Step 3

## Detail 46B NTS


**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## PARAPET / HANDRAIL TO WALL JUNCTION ENVIRO Panel Capping Step 4

## Detail 46C NTS

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**




## DECK / PERGOLA EXTERIOR Wall Fixing

## Detail 47 Scale 1:5

Note: Detail to be drawn to specific design

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME


**NOTE:** If you are using a short window support bar or no support bar is required under the window then you must use DPC under the window sill. **OPTION 1:** It is acceptable to have both the DPC and support bar installed together. See below.



## OPENING FLASHINGS Alternative Window Sill

**Detail 48 Scale 1:2**


### MASON'S ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## GENERAL LAYOUT AND AIRFLOW

## Detail 49 NTS

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME




## CONTROL JOINT Mid-Floor

(Required where timber joists are not seasoned or wall height exceeds 10m)

**Detail 50 Scale 1:5 & 1:2**


## MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## ROOF/WALL JUNCTION - KICKOUT FLASHING

**Detail 51 NTS**

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME




## OPENING FLASHING - CONCRETE DOOR SILL With Rebate

**Detail 52 Scale 1:2**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**






**OPENING FLASHING -  
CONCRETE DOOR SILL  
Without Rebate**

**Detail 53 Scale 1:2**


**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## OPENING FLASHING - TIMBER DOOR - Sill

**Detail 54 Scale 1:2**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**




## OPENING FLASHING Door - Sill 3D

MASON'S PVC Corner Guard


**Detail 55 NTS**

**MASON'S ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## UPPER RAKING SOFFIT Metal Flashing


## Detail 56 Scale 1:5



## UPPER RAKING SOFFIT Hidden Flashing

## Detail 57 Scale 1:5


### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME



## OPENING FLASHING - WINDOW HEAD - Monotek

**Detail 58 Scale 1:2**

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME




## OPENING FLASHINGS ENVIRO AAC PANEL / MONOTEK Vertical Junction For Above Windows & Doors

**Detail 59 Scale 1:2**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**

**NOTE:** If you are using a short window support bar or no support bar is required under the window then you must use DPC under the window sill. Option 1: It is acceptable to have both the DPC and support bar installed together.




## OPENING FLASHINGS

### Window Sill with DPC Flashing

### OPTION 1

**Detail 60 Scale 1:2**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



**Soffit Edge**

**Detail 61 Scale 1:2**

**MASON'S ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**



## PRE-CLADDING CHECKLIST

### For builders, trained installers and building inspectors

Consent No		
Start Date		
Client Name		Phone <span style="border-bottom: 1px solid black; width: 100px;"></span>
Builder		Phone <span style="border-bottom: 1px solid black; width: 100px;"></span>
Architect		Phone <span style="border-bottom: 1px solid black; width: 100px;"></span>

Owner/ Builder must have the framing and other components of the building correctly installed to enable the installation of the ENVIRO AAC Panel system.  
Refer to page 4, Scope and Limitations

Tick  
Box



**Special Attention should be made for:**



**Floor Slab Layout**

- Ensure distance from outside of framing to outside of concrete footing is exactly 95mm on all sides of building. If slightly under it is okay on single storey only. This allows 45mm for the cavity and 50mm for the ENVIRO Panels. 38mm batten ties will be used where 7mm brace ply is required.
- Ensure ground level is 250mm below floor level, min. 300mm out around base to allow for plastering.



**Rebate**

- Install MASONS Dryfix DPC as per manufacturers specifications
- Smooth and level



**Framing - All Straight and level**

- Studs straightened for wall lining before ENVIRO Panels are installed
- Internal corners – supply and install 1 stud or full length H3.2 45x45mm ENVIRO Tie, 200mm from internal corner



**Wall Wrap is MASONS Barricade Building Wrap**

- Exterior timber framed walls must be wrapped with MASONS Barricade Building Wrap which complies with compliance document E2/AS1 table 23. MASONS Barricade Building Wrap must be fixed to the exterior wall framing prior to installation of AAC ENVIRO Ties.
- Ensure MASONS Barricade Building Wrap is continuous around corners and installed horizontally.
- Ensure that all penetrations such as waste water pipes and the like have been flashed to the building wrap using "approved flexible flashing tape"

## MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME

☐ **Head Flashing's**

- Cut aluminium powder coated z-flashings 20mm either side of outside flange of windows. These will need to be cut and turned up to form stop ends and sealed with BOSTIK safe seal.
- MASONS Barricade Tape has been dressed over z-flashing and onto MASONS Barricade Building Wrap.
- Need to ensure the application of 3mm wide by 3mm thick Inseal-3259 single sided foam tape to the top edge of the window and door joinery before installation of head flashing.

☐ **Windows**

- Window distance from framing – minimum 47mm from outside of framing to inside flange of window
- The manual states throughout that continuous support bars are to be used on all windows, however if for any reason there is a requirement to use short support bars then Masons Dry fix DPC must be placed underneath the bottom of the windows

☐ **Joinery**

- All joinery must be set into openings minimum 47mm from outside of framing to inside flange of window. This allows 10mm of the joinery bearing over the ENVIRO Panel.
- The builder is also responsible for the application of approved flexible flashing tape around openings prior to the installation of any joinery.

☐ **If Two Storey**

- Check with Builder that all waterproofing details including roof junctions, flashing's and diverters have been done
- All protective sheeting is on roof
- Scaffolding

**All Plumbing including Gas lines, need to be pressure tested prior to installation of internal linings. MASONS Plastabrick will not be responsible for replacement of internal linings if this is not done.**

**Variables / Concerns / Comments:**

---

---

---

---

---

---

---

---

---

---

**Builder/Owner:** \_\_\_\_\_ **Signed:** \_\_\_\_\_

**PLEASE CONTACT LOCAL DISTRIBUTOR BEFORE JOINERY IS PRODUCED**

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**

## PRE-COATING CHECKLIST

### For trained installers, plasterers and building inspectors

Consent No \_\_\_\_\_

Start Date \_\_\_\_\_

Client Name \_\_\_\_\_ Phone \_\_\_\_\_

Builder \_\_\_\_\_ Phone \_\_\_\_\_

Architect \_\_\_\_\_ Phone \_\_\_\_\_

Tick  
Box



MASONS Plastabrick recommends an inspection by Building Inspector prior to plastering

- ☐ - Panels must be flat and straight with min. 6 screws per sheet, countersunk 10mm max and no closer than 50mm from edge of panel.
- ☐ - Ensure all exposed steel ends are treated with CRC zinc anti corrosion paint.
- ☐ - All external and internal Brick Veneer to AAC Panel corners are filled with expandable foam.
- ☐ - Vents - 40mm round holes are drilled into the bottom of the panel at max. 1200 centres for aluminium vents. These are then placed in after plastering, before painting.
- ☐ - Ensure that sill flashing's are in place and sealed with BOSTIK safe seal at corners.
- ☐ - Ensure window head flashing is fixed in place, level and straight.
- ☐ - MASONS base shoe / cavity closer should be adhered with BOSTIK safe seal and fixed in a straight line to bottom edge of panel where required
- ☐ - Sill and base shoe flashing's primed with Plasta Seal and coated with MASONS meshing render
- ☐ - Ensure roof flashing's are in place and checked by Builder and Building Inspector prior to plastering where relevant.
- ☐ - All pipe work/ penetrations through cladding are filled with Low expandable foam and sealed with BOSTIK safe seal sealant.

Note: PVC Reveal Bead Flashing is installed by plasterers when masking windows

Variables / Concerns / Comments:

---

---

---

---

---

---

---

---

ENVIRO Panel Installer: \_\_\_\_\_ Signed: \_\_\_\_\_

Approved by \_\_\_\_\_ Position: \_\_\_\_\_ Signed: \_\_\_\_\_

### MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME

## FINAL CHECKLIST

### For trained installers, plasterers and building inspectors

Consent No \_\_\_\_\_

Start Date \_\_\_\_\_

Client Name \_\_\_\_\_ Phone \_\_\_\_\_

Builder \_\_\_\_\_ Phone \_\_\_\_\_

Architect \_\_\_\_\_ Phone \_\_\_\_\_

Tick  
Box



- ☐ - Specified number of render coats have been applied. Finish to manufacturer's specifications
- ☐ - MASONS Corner beads have been used
- ☐ - Specified review of coating system has been applied and finished to manufacturer's standard

Variables / Concerns / Comments:

---

---

---

---

---

---

---

---

ENVIRO Panel Installer: \_\_\_\_\_ Signed: \_\_\_\_\_

Approved by \_\_\_\_\_ Position: \_\_\_\_\_ Signed: \_\_\_\_\_

**MASONS ENVIRO AAC ON 45mm CAVITY  
TIMBER FRAME**