

PEF Rod

P.E.F. Foam Backer

Masons™ PEF Rod is a cylindrical flexible closed cell polyethylene material, available in various diameters from 6mm to 50mm.

Applications

- Masons PEF Rod is used around windows, doors or other penetration openings. It ensures the sealant does not completely fill the cavity.
- Limits the amount and depth of the sealant applied into the joint.
- Acts as a bond break to allow joint movement without undue stress to sealant.
- Acts as a barrier to the flow of sealant through a joint.
- Will assist in providing an around the window frame and penetrations through walls.
- For use with pre-cast concrete slabs and joints between brick and masonry.

Physical Properties

- Weather resistant
- No water absorption, closed cell
- Easy to install from dispenser box
- Wide range of sizes available
- Non toxic, odourless
- Resistant to most chemicals
- Easily compressible, good expansion
- Very light weight

Diameter	Roll Length	Masons Code
6mm	20m	Air Tight6X20
6mm	50m	Air Tight6X50
8mm	20m	Air Tight8X20
8mm	50m	Air Tight8X50
10mm	20m	Air Tight10X20
10mm	50m	Air Tight10X50
13mm	20m	Air Tight13X20
13mm	50m	Air Tight13X50
15mm	20m	Air Tight15X20
15mm	50m	Air Tight15X50
20mm	20m	Air Tight20X20
25mm	10m	Air Tight25X10
30mm	10m	Air Tight30X10
40mm	5m	Air Tight40X5
50mm	5m	Air Tight50X5

