




- 45x45 H3.2 AAC ENVIRO Tie
- kept 100mm min above wedge
- MASONS Barricade Building Wrap
- H3.2 timber wedge with 15° slope
- MASONS Barricade PLUS Tape over wedge adhered to MASONS Barricade Building Wrap
- MASONS Barricade PLUS Tape to meterbox perimeter adhered to MASONS Barricade Building Wrap



- 45x45 H3.2 AAC ENVIRO Tie
- 50mm AAC ENVIRO Panel
- MASONS AAC render & coating system
- Blocking between studs
- H3.2 timber wedge with 15° slope to direct water to outside edge. Masons Barricade PLUS Tape over top adhered to MASONS Barricade Building Wrap
- PVC reveal bead flashing adhered to face of meter box. BOSTIK safe seal over and plastered in.
- Low expandable foam backing
- MASONS Barricade PLUS Tape adhered to MASONS Barricade Building Wrap & meter box
- PVC reveal bead flashing adhered to face of meter box. BOSTIK safe seal over and plastered in.
- 45x45 H3.2 AAC ENVIRO Tie
- MASONS Barricade Building Wrap over thermal break



MASONS Barricade PLUS Tape to perimeter of Meter Box



MASONS Barricade Building Wrap

## METER BOX Detail 36 NTS

## METER BOX

## Detail 35 Scale 1:5

### MASONS ENVIRO AAC ON 45mm CAVITY STEEL FRAME