


- MASONS Barricade PLUS Window Tape over flashing onto MASONS Barricade Building Wrap extended 20mm each side of opening
- 14gx75mm Bugle Head Type 17 Screws embedded 10mm max. into panel. Min 50mm from edge.
- MASONS AAC render & coating system
- 50mm AAC ENVIRO Panel
- MASONS Barricade PLUS Window Tape
- Turn up ends of head flashing 20mm
- Approved foam tape adhered to top of window flange
- 10mm Min
- Aluminium Window Head Moulding Flashing with 15° Fall to be installed by builder
- MASONS Barricade Building Wrap




Note: MASONS Sill and base shoe flashings must be primed with Plasta Seal and coated with MASONS meshing render

OPENING FLASHING Window Head

Detail 19
Scale 1:2

- MASONS Barricade Building Wrap
- MASONS Barricade PLUS Window Tape over flashing onto MASONS Barricade Building Wrap extended 20mm each side of opening
- Turn up ends of head moulding 20mm
- BOSTIK Safe Seal flexible sealant
- Aluminium Window Head Moulding Flashing with 15° Fall to be installed by builder
- Approved foam tape adhered to top of window flange
- MASONS Barricade PLUS Window Tape



OPENING FLASHING - 3D View

Detail 20 NTS

MASONS ENVIRO AAC ON 45mm CAVITY TIMBER FRAME