Monier[™]

PRODUCT TECHNICAL STATEMENT

CONCRETE

HACIENDA

01. INTRODUCTION

Hacienda is a versatile profile that combines traditional good looks with exceptional product performance. The Hacienda profile can complete many different looks such as a Modern, Mediterranean or Traditional style home. Further technical resources are provided at monier.co.nz/Technical

02. BUILDING CODE COMPLIANCE

Monier Hacienda Concrete Roof Tiles conform to the NZBC (New Zealand Building Code) requirements and when installed according to Monier's instructions and NZBC, meet the following provisions:

- NZBC Clause B2 Durability
- NZBC Clause E2 External Moisture

03. SCOPE OF USE AND LIMITATIONS

Specific design requirements for Hacienda Tiles:

- Minimum roof pitch 15°
- Roof underlay is mandatory for any roof:
- receiving discharge from a spreader,
- on a skillion roof,
- on roofs in wind zone Very High or Extra High, or
- where roof pitch is below 20°;

however highly recommended in all installations.

• Maximum rafter length varies with roof pitch as follows:

INSTALLED WITH UNDERLAY

Roof Pitch	Max. Rafter Length (m)	Roof Pitch	Max. Rafter Length (m)	Roof Pitch	Max. Rafter Length (m)
15°	4.5	22°	8.0	29°	11.5
16°	5.0	23°	8.5	30°	12.0
17°	5.5	24°	9.0	31º	12.5
18°	6.0	25°	9.5	32°	13.0
19°	6.5	26°	10.0	33°	13.5
20°	7.0	27°	10.5	34°	14.0
21°	7.5	28°	11.0	35°	14.5

Please refer to the Design Guide available at monier.co.nz/Technical for further information regarding:

- Wind and Terrain Categories
- Specific details on when underlay is required
- Rafter and truss spacings and batten requirements
- Batten installing requirements



04. CONSENTING INSTRUCTIONS


When consenting, it should be verified that the designer has assessed:

- Fixing and underlay requirements with regard to Wind and Terrain categories
- Batten sizes relative to rafter spacings
- Maximum rafter length for the roof pitch
 Detailed guidance is provided in the Design Guide available at monier.co.nz/Technical.

05. STANDARDS

Tiles are manufactured to AS 2049 / NZS 4206.

06. PRODUCT DETAILS



Tile coverage (+/- 2%)	Approx. 11 tiles/sqm		
Dimensions (+/- 2%)	Length: 420mm Width: 329mm		
Weight (+/- 2%)	Per tile: 4.5kg Per sqm: 49.5kg (80mm lap)		
Head lap adjustment (mm)	78 – 125		
Recommended bonding	Straight Bond		
Roof pitch	Minimum with underlay 15° Minimum without underlay 20° Please refer to the Monier Construction Requirements at monier.co.nz for installation requirements applicable to your project		

Find out more on **monier.co.nz** or call us on 0800 666 437




Monier[™]

PRODUCT TECHNICAL STATEMENT


CONCRETE ACCESSORIES

PARBARGE




Length	Width	Height	Angle	Weight
(mm)	(mm)	(mm)	(Degree)	(kg)
420	248	126	84	4.9

RIDGE



Length	Width	Height	Angle	Weight
(mm)	(mm)	(mm)	(Degree)	(kg)
420	250	80	120	3.4

3-WAY APEX (STANDARD RIDGE)



Length	Width	Height	Angle	Weight
(mm)	(mm)	(mm)	(Degree)	(kg)
391.7	413.3	135	135	3.8



07. INSTALLATION

Refer to Monier's website, "Find a Supplier" list of experienced and qualified Roofing Specialists to ensure your tiles are installed professionally and to the appropriate standard.

Further information is provided in the Installation Guide available at monier.co.nz/Technical.

08. WARRANTY

Monier Hacienda Roof Tiles are structurally guaranteed to perform their function and are a low maintenance roof cladding option.



09. MAINTENANCE

Caution should be exercised by any persons needing to access the roof once it is installed.

Details regarding access and recommended maintenance are provided at monier.co.nz/Maintenance.

10. HACIENDA COLOUR RANGE*





*Some colours are subject to a longer lead time.
Tile colour may vary from printed brochure.

Find out more on **monier.co.nz** or call us on 0800 666 437

