

DC700G-CM

Door closer with Cam-Motion® technology and integrated Close-Motion® element




ASSA ABLOY DC700G-CM

- Door closer with Cam-Motion® technology, extended mounting plate and integrated Close-Motion® element for safe and noiseless closing
- The door can be pulled closed safely and quietly from an angle of $\leq 10^\circ$
- Suitable for retrofitting on fire doors and smoke control doors and fastening using drilling template in accordance with DIN EN 1154, supplementary sheet 1:2003-11
- Suitable for fire and smoke protection doors with tamper protection
- Tested as a whole element in accordance with EN 1154, size 3-6
- For single action doors up to 1400 mm wide
- Tested according to EN 1155 and EN 1158 (CE certificates applied for)

Characteristics of DC700G-CM

- Integrated Close-Motion® element in extended closer housing
- Close-Motion® element with horizontal and vertical adjustment
- Optional tamper protection, installation without dismantling function elements
- Standard installation on hinge side
- Can be used for left and right-handed doors
- 14 mm height adjustable arm system for ease of fitting
- Closing speed and latching speed continuously adjustable from front
- Variable adjustable closing force
- Opening angle up to 170°
- Thermodynamic valves for consistent speed
- Standard colours: Silver EV1, stainless steel design



Characteristics of G150

- Close-Motion® control curve integrated in the guide rail
- Drilling template of the standard guide rails from ASSA ABLOY can be used
- Height-adjustable by 2 mm for tolerance
- Concealed fastening screws

