



Cavity battens
Refer V00 Batten Options

Note: Underlay strips to isolate aluminium from treated timber battens
Refer V00

Ulltraclad© UA 7584 Window Jamb / Sill mitred in corners

Corners held together with PVC corner gusset Part No. CLADSTAKECNR

Building underlay

Vertical track flashing 0.9 mm folded aluminium flashing (hemmed) to 150 mm above window head or inter-storey
Alternatively use Dynex Dynaflash

Window support bar for window openings wider than 600 mm. Support bar to comply with E2/AS1 9.1.10.5(v).
Install batten below if required

Flexible flashing tape along sill to continue 50 mm onto face of wall and 100 minimum up each Jamb

Note: Underlay strips to isolate aluminium from treated timber battens
Refer V00

ULLTRA CLAD[®]
ALUMINIUM WEATHERBOARDS

ULLTRA CLAD ALUMINIUM CO LTD
PO Box 98 843 Manukau City Auckland 2241
118 Wiri Station Road Wiri 2104 New Zealand
TL 09 262 6262 Ext. 814 Mob 021 541 563
www.ulltraclad.co.nz
© ULLRICH ALUMINIUM - All Rights Reserved

H12
Rev : 10

Sill-Jamb on Cavity
UA 7726 SHADO 100 BOARD

HORIZONTAL CAVITY SYSTEM
Scale: 1 : 3 @ A4 - 2019

Branz Appraisal #487 2019. (Horizontal)