



# DATA SPECIFICATION

## METRO SERIES DOUBLE HUNG WINDOWS

### MAIN FEATURES

- For residential, commercial and institutional use
- A counter-balanced, double hung system where both panels move together
- A good option for non-projecting ventilation
- In fully open position with both sashes adjoining each other half the window area is open
- Generally appropriate in single banks because of the large width of coupling bars.

### FRAME TYPES

**Contemporary Frame** with flat, clean face for a modern appearance.

### SASH TYPES

**Double Glazed** for IGU thickness 24 - 30mm.

### FLASHINGS

VANTAGE has a range of standard flashings.

### FINISH / COLOUR

**Powder Coated** in a wide range of colours.

**Anodised silver** or bronze as standard, 12 micron thickness. Other colours and thicknesses are available.

### GLASS

Double glazed units 24mm thickness are generally used, with a maximum of 30mm. The full range of glass types can be included in this product. For further information consult your local VANTAGE manufacturer.

### PERFORMANCE

VANTAGE complies with NZS4211: 2008 Performance of Windows. Certificates provided on request.

A guarantee for all VANTAGE products is provided under normal conditions of use against failure of materials and workmanship for five years from the date of practical completion.

### SIZES

Weight restriction per panel 100kg. Recommended aspect ratio 2:1.

### HARDWARE

Double hung windows are fitted with an Urbo half handle in the bottom rail which activates two-point locking at the sill.