



MAIN FEATURES

- Maximum door panel height of 2.2m.
- Made with aluminium cladding, these doors offer an elegant, low maintenance alternative to timber doors.
- Custom made in a range of designs.
- Applied mouldings are used with solid or glazed panels.
- Aluminium construction for greater stability and no warping.
- Matching sidelight options - opening or fixed.
- Double glazing, leadlight and other decorative glass panels available.
- Wide powder coat colour range available.
- Wide range of lock options.
- Two moulding options: traditional or contemporary.

NOTE: Classic Collection aluminium entrance doors have polystyrene core panels. Matching sidelights can be supplied. These sidelights can either be fixed or opening similar to a French door. This allows a full width opening to be achieved when required.

FRAME TYPES

Open Out box section door frame.

Open In box section door frame.

MULLION AND TRANSOMS

Sidelight Mullion / Overlight Transom, box section, bead glazed for maximum 6.38mm single glazing, 22mm double glazing or solid panel.

Heavy Duty Mullion / Overlight Transom, box section, bead glazed for maximum 6.38mm single glazing and 22mm double glazing.

TOP AND BOTTOM RAILS

Pocket Glazed for solid panels.

DOOR STILES

Hinge / Lock Stile, pocket glazed.

Lock Rebate Meeting Stile, pocket glazed.

Keeper Rebate Meeting Stile, pocket glazed.

SIDELIGHTS

Sidelight Rail (62mm) for single and double glazing.

Wide Sidelight Rail (118mm) for single and double glazing.

FLASHINGS

Classic doors will usually be installed in sheltered places. However, for there is a range with standard flashing available for exposed sites.

FINISH / COLOUR

Powder Coated in a wide range of colours.

GLASS

The solid infill panels are 18mm thick, consisting of 1.2mm aluminium-faced, high density, styrofoam core panels. Powder coat finish to match stiles and rails.

Double glazing (maximum 18mm), leadlight and other decorative glass panels are available. No glazing vinyls are visible on the outside of a Classic door (they are hidden from view). Contact your local manufacturer about the range of glass options.

PERFORMANCE

A guarantee for all our Entrance Doors is provided under normal conditions of use against failure of materials and workmanship for five years from the date of practical completion.

SIZES

Classic door panel sizes can range from (1800 x 710) to (2200 x 960).

HARDWARE

A range of lever handles and mortice locksets are available. Ask your local manufacturer about the surface finishes and styles available.