



MAIN FEATURES

- Aluminium clad doors combining tongue and groove boards (100mm wide) within a border of strong rails and stiles.
- Glass inserts (18mm double glazing only) are available with a flat-faced contemporary moulding as standard.
- Boards can be vertically or horizontally aligned.
- Doors are supplied fully built, but there is potential for on-site trimming where required.
- Maximum door size supplied is 2150mm (high) x 960mm (wide).
- Matching pairs of doors (i.e. French doors) are available in either half size or full size panel options, allowing for wide entry access (minimum sidelight width 310mm).
- Doors are filled with high density styrofoam for thermal efficiency and sound dampening.
- Thermally broken stiles and rails can be included as an option - also allowing dual colour doors.
- A wide range of door handle and lock options is available. Four-point locking can be included. Hardware choice must be advised at time of order.
- The dense, rigid construction means that Latitude doors rate highly for impact resistance and jimmy resistance.

FRAME TYPES

Open Out box section door frame.

Open In box section door frame.

MULLIONS AND TRANSOMS

Sidelight Mullion / Overlight Transom, box section, bead glazed for maximum 6.38mm single glazing, 24mm double glazing.

Heavy Duty Mullion / Overlight Transom, box section, bead glazed for maximum 6.38mm single glazing, 24mm double glazing.

FLASHINGS

Latitude doors will generally be installed in sheltered places. However, there is a range with standard flashing available for exposed sites.

FINISH / COLOUR

Powder Coated in a wide range of standard colours.

GLASS

Double glazed units are used as standard with a thickness of 18mm. Glass inserts are bead glazed and no glazing vinyls are visible. Contact your local manufacturer about the range of glass options.

PERFORMANCE

A guarantee for all our Entrance Doors is provided under normal conditions of use against failure of materials and workmanship for five years from the date of practical completion.

SIZES

Latitude doors are available in a range of sizes with the maximum dimensions being 2150mm (high) x 960mm (wide). There is potential for on-site trimming where required.

HARDWARE

A range of lever handles and mortice locksets as well as gripsets are available. Four point locking can be included. Hardware choice must be advised at time of door order.