

DATA SHEET

issue 04/17

EverTread

Entrance System

pg 1/2

Manufacturer

Advance Flooring Systems Limited

Trade Name

EverTread

Product Description

An 17mm deep aluminium strip mat system with polyamide inserts for entrance areas.

Product Benefit

EverTread is an entrance mat system engineered to trap soiling and moisture that is easy to clean and protects flooring surfaces inside. EverTread has fully interlocking aluminium base that eliminates additional moisture through by specially designed molded feet and can handle medium rolling loads.

EverTread provides excellent slip resistance mitigating the risk of slips and falls causing injury.

Area of Application

EverTread is ideal for extreme levels of foot traffic for any commercial entry application such as commercial premises, hotels and tertiary education facilities. EverTread is to be used indoors or in weather protected areas.

Composition

EverTread is manufactured with continuous anodised aluminium interlocking strips, molded anti-clatter feet and polyamide carpet inserts.

Dimensions

Strip depth 17mm Overall tread size 40mm

Appearance

Natural anodised aluminium interlocking strip system available in a range of 8 polyamide insert colours.

Manufacture

EverTread is manufactured by Advance Flooring systems to its copyright design.

Smoke/Fire

The EverTread matting system has been tested and exceeds the AU & NZ requirements.

Slip Test

EverTread has been tested and exceeds the AS/NZS 4586: 2004 NZ & AS 4586: 2013 AU requirements.

Advance Flooring Systems Ltd email: info@advanceflooringsystems.com www.advanceflooringsystems.com

NZ: 0508 238 262 AU: 1800 459 682





DATA SHEET

issue 04/17

EverTread

Entrance System

pg 2/2

Durability

Extra Heavy Commercial.

UV Resistance

Some fading of the polyamide carpet inserts may be observed in areas of intense sunlight. Aluminium sections are not affected.

Sustainability

Advance Flooring Systems is committed to the protection of the environment. EverTread is designed to minimise environmental impacts during manufacture and engineered to last a long first lifecycle supported by a 15 year warranty.

Installation

EverTread tiles must be installed by a competent and experienced installer, more information on the recommended installation procedures is available on our website <u>www.advanceflooringsystems.com</u> or upon request.

Cleaning and Maintenance

EverTread has low maintenance requirements and can be removed for cleaning as excessive dirt if required. Special dirt collection zones and polyamide infills gather dirt for simple and effective cleaning. *Daily Maintenance*: Vacuum EverTread thoroughly with a powerful vacuum cleaner preferably with power driven brushes. This agitates the pile to loosen the trapped dirt.

Periodic Maintenance: A routine visual inspection will identify when EverTread is becoming embedded with dirt which can be removed by a water spray extraction method. Alternatively, EverTread can be scrubbed by machine or hand, rinse thoroughly using a wet and dry vacuum cleaner. In cases of staining, household solvents may be used, however must only be applied to a rag and rubbed onto the pile. Do not pour solvents directly onto the mat as a breakdown of the infill adhesive may result. More information on the recommended maintenance procedures is available on our website www.advanceflooringsystems.com or upon request.

Warranty

Advance Flooring Systems provides a fifteen (15) year product warranty, that the product will be free of manufacturing defects and the product is maintained according to the manufacturers maintenance instructions, subject to fair wear and tear.

Advance Flooring Systems Ltd email: info@advanceflooringsystems.com www.advanceflooringsystems.com

NZ: 0508 238 262 AU: 1800 459 682

