

















Specifications

DESCRIPTION	NORM	DATA
Pile Fiber		100% Polyamide (Solution Dyed)
Gauge		1/10 loop pile
Tuft Density	ISO 1763	106 600 Stitches/m ²
Total Pile Mass	ISO 8543	740 g/m ²
Mass of Pile above the Substrate	ISO 8543	430 g/m ²
Thickness of Pile above the Substrate	ISO 1766	3,7 mm
Surface Pile Density	ISO 8543	0,116 g/cm ³
Total Weight	ISO 8543	4640 g/m ²
Total Thickness	ISO 1765	8,0 mm
Primary Backing		Non-woven primary backing
Backing		Vinyl backing reinforced with glass fiber (100 % recycled PVC)
Tile Size		50x50cm
Tiles per Box		20 = 5m ²
Installation		
Printing Facilities		NO



Technical Performances

RHO-LRV				Classification EN 1307 - 33 / Commercial Heavy Luxury Class – LC2			
7 Colors	%						
026	4,6%			Classement UPEC NF 262 - U3SP3E1C0 (Certificate n° 349T-006.1) Fire rating EN 13501-1: BflS1			
034	8,7%						
036	4,3%						
046	5,1%	Heated Floor 		Impact Noise Reduction 		EN ISO 10143-3 $\Delta L (w) 26 \text{ dB}$	
065	7,8%	ISO 10456 0,11 m ² K/W					
097	4,0%	Electrostatic prop. 		ISO 6356 $\leq 2,0\text{kV}$		Sound Absorption 	
136	6,7%	ISO 10965 $RT \approx 10^{10}\Omega$				ISO 11654 $\alpha_w = 0,15 (H)$	
		Dimensional Stability 		EN 986 $\leq 0,10\%$		Color Fastness 	
				EN 105 - B02		7/8	
				N° 0679-CPR-0196 07 EN 14041: 2004		Castor Chair 	
						EN 985 Passed $R \geq 2,4$	



The above information is subject to modifications for the benefit of further improvement. (Updated on 13/01/2017)

TECSOM - 3800 CROSS



Advance Flooring Systems Ltd
email: info@advanceflooringsystems.com
www.advanceflooringsystems.com

Call us: **0508 238 262**

