

BPIR Data Sheet

ScrapeRIB

1/2

Product class

Class 1 - Batch or mass-produced products

Product name

ScrapeRIB - Entry Carpet System

Place Manufactured (New Zealand or Overseas)

Italy

Product description and its intended use

ScrapeRIB is a durable polypropylene needle rib entry carpet bonded to a SBR latex primary backing system.

Relevant Building Code clauses**B2****Durability**

Performance clause B2.3.1 c) 5 years

C3**Fire Affecting Area beyond the source**

Performance clause C3.4 b) - does not apply to detached dwellings, within household units in multiunit dwellings or outbuildings and ancillary buildings.

D1**Access Routes**

Performance clause D1.3.3 d)

F2**Hazardous Building Materials**

Performance clause F2.3.1

Statement of how the building product is expected to contribute to compliance**B2****Durability**

B2.3.1 c)

ScrapeRIB entry carpet has a durability beyond 5 years, based on NZBC B2/VM1 clause 1.1 In-service history.

Durability supported by a 2 year product warranty.

C3**Fire Affecting Area beyond the source**

C3.4 b)

ScrapeRIB has been tested to AS ISO 9239.1 - 2003 and achieves a CHF (Critical Heat Flux) mean of 5.2kW/m². Refer to CRET Product Testing, Test Report RL2013/300-1, dated 05.09.2023.

D1**Access Routes**

D1.3.3 d)

ScrapeRIB meets the requirements for slip requirements for slip resistance in accordance with NZBC D1/AS1 2.1 Slip Resistance, Table 2 Slip Resistance for walking surface. ScrapeRIB is acceptable for level and sloping surfaces, wet and dry slip resistance.

F2**Hazardous Building Materials**

F2.3.1

ScrapeRIB is manufactured from non-toxic materials.

We are here to help you, if you have any questions or require further clarification please contact us.

BPIR Data Sheet

ScrapeRIB

2/2

Limitations on the use of the building product

- ScrapeRIB entry carpet are not suitable for exterior, weather exposed applications. Suitable for interior or weather protected areas only.

Design requirements that would support the appropriate use of the building product

- NA

Installation requirements

- Install in accordance with Advance Flooring, Installation Instructions - ScrapeRIB.
- Recommended to be installed with an Advance Flooring matwell surround frame.
- After frame installation, prepare substrate base to suit depth of matting and to provide a smooth, level base.

Maintenance requirements

- Maintenance to be in accordance with Advance Flooring, Maintenance Instructions - Advance Entry Carpet.
- Daily maintenance - soiling removed with vacuum cleaner. Chewing gum to be removed as soon as it appears by use of specialist products.
- Periodic maintenance - carry-out routine visual inspection to identify when matting is becoming full of dirt. Clean using water spray extraction method. Can be scrubbed by machine or hand along direction of infills. For staining, household solvents may be used to manufacturer's instructions. Only used solvents applied with a rag, do not pour solvent onto matting.
- The matting can be removed from the well and sprayed with a medium pressure water machine.
- If inserts are damaged or unduly worn, they can be replaced.

Building Act 2004 section 26 compliance

- Yes/No