

BPIR Data Sheet

tretford, roll, tile & custom rugs

1/1

Product class Class 1 - Batch or mass-produced products	Product description and its intended use tretford is constructed from over 70% natural Cashmere goat hair. Ethically sourced through goat-herding communities in Mongolia, it is a unique ribbed construction available in a range of 60 colours. Roll is 2m wide with no fixed length, tile is 500x500mm and rugs are all custom made to size.
Product name tretford - Roll, Tile and Custom Rugs	
Place Manufactured (New Zealand or Overseas) Overseas, manufactured in Germany	

Relevant Building Code clauses

B2	Durability	Performance clause B2.3.1 c) 5 years
C3	Fire Affecting Area beyond the source	Performance clause C3.4 b) - does not apply to detached dwellings, within household units in multiunit dwellings or outbuildings and ancillary buildings.
F2	Hazardous Building Materials	Performance clause F2.3.1

Statement of how the building product is expected to contribute to compliance

B2	Durability - B2.3.1 c)	tretford has a durability beyond 5 years, based on NZBC b2/ VM1 clause 1.1 In-service history.
		Durability supported by a 5-year product warranty.
C3	Fire Affecting Area beyond the source - C3.4 b)	tretford flooring has been tested to EN ISO 9239.1 - 2010 (Flux) mean 7.6 kW/m2. Refer to APL Test Report 161486NZ dated 4 August 2016.
F2	Hazardous Building Materials - F2.3.1	tretford carpet is certified Global GreenTag Level A.

We are here to help you, if you have any questions or require further clarification please contact us.

BPIR Data Sheet

tretford, roll, tile & custom rugs 1/1

Limitations on the use of the building product

- Suitable for interior applications only.

Design requirements that would support the appropriate use of the building product

- tretford is suitable for all areas requiring a durable, colourful sustainable carpet surface

Installation requirements

- Install in accordance with Advance Flooring tretford Installation Instructions
- Ensure substrate is smooth, dry, clean, and free from contamination. For internal applications ensure substrate does not vary from required level by no more than 4mm measured under a 4m straight edge.
- Substrate must have a relative humidity of 75% or below
- Must be laid with using adhesive specified and recommended by Advance Flooring

Maintenance requirements

- Maintenance to be in accordance with Advance Flooring, guide tretford carpet.
- Regular maintenance – vacuum often