



Technical Data Sheet



	Standard	Result
Size	ISO 24342	See separate table
Thickness	ISO 24346	2.5 mm
Wear layer	ISO 24340	0.5 mm
Surface treatment		K-Guard+ PU coating
Warranty ¹	Commercial Domestic	15 years wear Lifetime wear
Bevelled edge		Micro
Standards	ASTM F1700	Pass
Classification	ISO 10874 - Commercial ISO 10874 - Domestic	33: Commercial heavy 23: Domestic heavy
Reaction to fire	AS/NZS 9239.1:2010	CRF: > 11 kW/m ² Smoke value: 93% min.
Staining resistance	EN ISO 26987/EN 423 ASTM F925	Excellent Pass
Light fastness	ISO 105-B02 ASTM F1515	Pass (≥ 7) Pass (< 8)
Abrasion resistance	EN 660-2 ISO 10582 ASTM D3884	Group T Type 1 Pass
Flexibility	ISO 24344	Pass
Dimensional stability	EN 434/ISO 23999 ASTM F2199	Pass (≤ 0.25%) Pass
Acoustic impact noise reduction ²	EN ISO 717-2/EN ISO 140-8	ΔL _w = 2 dB
Electrical behaviour body voltage	EN 1815	Pass
Indentation - residual	EN 433/ISO 24343-1 ASTM F1914	Pass (≤ 0.1 mm) Pass (< 8%)
Castor chair continuous use	EN 425/ISO 4918	Pass
Thermal resistance	ISO 8302	0.0097 m ² K/W Suitable for underfloor heating. Max 27°C
Slip resistance ³	AS/NZS 4586:2013	See separate table
Adhesive	General use: High temperature:	Karndean Mega-Bond Karndean 8000 2-part Polyurethane
Environmental	GBCA/NZGBC GreenStar Rating System Floorscore SCS-EC10.3-2014 v4.0 Indoor Air Comfort Environmental Product Declaration NSF/ANSI 332 ISO 14001 / ISO 9001	GreenTag Level A; LCA Silver Plus; Best Practice PVC Indoor air quality certified; Compliant low emitting VOC emissions. Gold certification Compliant low emitting VOC emissions. Product-specific Type III EPD (products with external third-party verification) Sustainability Assessment for Resilient Floor Coverings; Conformant product Manufactured to quality and environment management systems standards
Recycling		Suitable
Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Result is Ln,w = 58 dB when installed on Regupol 4515 acoustic underlay

³ Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Australia

Call: 1800 33 11 70
Email: customerservice@karndean.com.au
Visit: www.karndean.com

New Zealand

Call: 0800 44 21 01
Email: customerservice@karndean.co.nz
Visit: www.karndean.com

Jun 22





	Product Code	Size		Box Quantity		Slip Resistance
		mm	inches	m ²	Pieces	Oil-Wet Ramp
Wood Designs	WP311	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP312	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP313	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP315	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP316	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP318	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP319	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP329	914.4 x 152.4	36" x 6"	3.345	24 Planks	R10
	WP411	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
	WP411-SRA	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R11
	WP413	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
	WP414	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10
WP421	1219.2 x 228.6	48" x 9"	3.345	12 Planks	R10	
Stone Designs	SP111	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10
	SP114	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10
	SP115	457.2 x 457.2	18" x 18"	3.345	16 Tiles	R10
	SP211	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP212	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP213	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP213-SR	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP214	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP215	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP216	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10
	SP217	457.2 x 609.6	18" x 24"	3.345	12 Tiles	R10