

Technical Data

	Standard	Result	Slip resistance	
			Product	Oil-Wet Ramp
Size	ISO 24342	See separate table	KP37	914.4 X 101.6 R9
Thickness	ISO 24346	2.0 mm	KP39	914.4 X 101.6 R9
Wear layer		0.3 mm	KP54-6	914.4 X 152.4 R10
Surface treatment		K-Guard® PU coating	KP55-6	914.4 X 152.4 R10
Warranty	Commercial	10 years light commercial*	KP91	914.4 X 101.6 R9
	Domestic	Lifetime wear*	KP94	914.4 X 152.4 R10
Bevelled edge		No	KP95	914.4 X 152.4 R10
Standards	EN 649/EN ISO 10582	Pass	KP96	914.4 X 152.4 R10
	ASTM F1700	Pass	KP97	914.4 X 152.4 R10
Classification		Commercial Light Duty use	KP98	914.4 X 152.4 R10
		Domestic Heavy Duty use	KP101	914.4 X 152.4 R10
Staining resistance	EN ISO 26987/EN 423	Excellent	KP103	914.4 X 152.4 R10
	ASTM F925	Pass	KP104	914.4 X 152.4 R10
Colour fastness to light	ISO 105-B02	≥6	KP107	914.4 X 101.6 R9
	ASTM F1515	<8	KP131	914.4 X 152.4 R10
Abrasion resistance	EN 660-2	Group T	KP136	914.4 X 152.4 R10
	ISO 10582	Type 1	KP137	914.4 X 152.4 R10
	ASTM D3884	Pass	KP138	914.4 X 152.4 R10
Flexibility	ISO 24344	Pass	KP139	914.4 X 152.4 R10
Dimensional stability	EN 434/ ISO 23999	≤ 0.25%	KP141	914.4 X 152.4 R10
	ASTM F2199	Pass	KP142	914.4 X 152.4 R10
Acoustic impact noise reduction	EN ISO 717-2 / EN ISO 140-8	ΔL _w = 1 dB**	ST5-18	457.2 X 304.8 R9
Electrical behaviour body voltage	EN 1815	Pass	ST8	304.8 X 304.8 R9
Indentation - residual	EN 433/ ISO 24343-1	≤ 0.1mm	ST9	304.8 X 304.8 R9
	ASTM F1914	<8%	ST11	457.2 X 304.8 R9
Castor chair continuous use	EN 425/ ISO 4918	Pass	ST12	457.2 X 304.8 R9
Thermal resistance	ISO 8302	0.0100 m²K/W	ST13	457.2 X 304.8 R9
		Suitable for underfloor heating	ST14	457.2 X 304.8 R9
Reaction to fire	AS/NZS ISO 9239.1:2010	CRF: 8.1 kW/m²	ST16	457.2 X 304.8 R9
		Smoke value: 42% min.	T88	304.8 X 304.8 R9
Slip resistance***	AS/NZS 4586:2013	See separate table	T89	304.8 X 304.8 R9
Adhesive	General use:	Karndean Mega-Bond	T98	304.8 X 304.8 R9
	High temperature:	Karndean 8000 2-part Polyurethane	T99-18	457.2 X 304.8 R9
Environmental	GBCA/NZGBC GreenStar Rating System	GreenTag Level 'A' + LCARate 'Silver Streamlined	T100	304.8 X 304.8 R9
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.		
	Indoor Air Comfort	Gold certification Compliant low emitting VOC emissions.		
	Environmental Product Declaration	Product-specific Type III EPD (products with external third-party verification)		
Recycling	NSF/ANSI 332	Sustainability Assessment for Resilient Floor Coverings; Conformant product		
		Suitable		
Phthalate free		Yes		

*Subject to terms

**Result is L_{n,w} = 58 dB when installed on Regupol 4515 acoustic underlay

***Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors including but not limited to: product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

Australia

Call: 1800 33 11 70

Email: customerservice@karndean.co.au

Visit: www.karndean.com

New Zealand

Call: 0800 44 21 01

Email: customerservice@karndean.co.nz

Visit: www.karndean.com