## RESIDENTIAL RT7 ROOFING RAKING INTERNAL GUTTER

80 mm

80 mm

mın

Detail Number: RI-RRTRO28A

Date drawn: 07/07/2017

Scale: 1:5@ A4

NOTES:

DESIGNER TO ENSURE DURABILITY OF FLASHING MATERIAL:

- I. SITUATION I: IN LOW, MEDIUM OR HIGH WIND ZONES, WHERE ROOF PITCH IS TO OR GREATER
- SITUATION 2: FOR ALL ROOF PITCHES IN VERY HIGH AND EXTRA HIGH WIND ZONES, FOR ALL WIND ZONES WHERE ROOF PITCH IS LESS THAN 10°.
- 3. SITUATION 3: FOR ALL ROOF PITCHES IN EXTRA HIGH WIND ZONES.
- EXCLUDES DRIP EDGE.

(6) X min 45

20

12° or greater

- INTERNAL GUTTER SHOULD BE MADE FROM NONFERROUS METAL COMPATIBLE WITH THE ROOFING MATERIAL
- GUTTER SHALL BE SIZED TO SUIT THE ROOF CATCHMENT AREA BUT SHALL BE NO LESS THAN THAN SHOWN IN THIS FIGURE AND DESIGNED IN ACCORDANCE WITH E2/AS I AND/OR THE NZ METAL ROOF \$ WALL CLADDING CODE OF PRACTICE.

SITE WIND ZONE		MINIMUM
(As per NZ53604)		Z
SITUATI	ON I (I)	50 <sup>(4)</sup>
SITUATI	ON 2 (2)	75 <sup>(4)</sup>
SITUATI	ON 3 <sup>(3)</sup>	90 (4)

SCREW FIXING UNDERLAY	2. 3. 4. 5.	
PRE-PRIMED TIMBERTEK \$ NEO WITH	G. RAFTER FOP PLATE	
25mm ALLOY EMBOSSED ———————————————————————————————————	GUTTER DEPTH	
	ROOF PITCH	Ī
	< 12°	Ī

HEM TO FLASHING

FDGF

ROOFING INDUSTRIES

## NOTES:

BARGE CAPPING

- These details are generally in compliance with E2/AS I and/or the NZ Metal Roof # Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

  Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof # Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

  Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof # Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

  Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof # Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof # Wall Cladding Code of Practice and In some cases specific details by 'Roofing Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof # Wall Cladding Code of Practice and In some cases specific details by 'Roofing Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof # Wall Cladding Code of Practice and In some cases specific details by 'Roofing Industries'

  These details are generally in compliance with E2/AS I and/or the NZ Metal Roof # Wall Cladding Code of Practice and In some cases are generally and the Parameter of the Parameter
- The building designer is ultimately responsible to ensure that details used meet the requirements of the NZ Building Code for the specific project.
- Details of the supporting structure including cavity battens are indicative only and are the responsibility of the building designer. For steel framed buildings thermal break cavity battens may be required.
- Underlay selection and building wrap types are the responsibility of the designer, Netting or other support is generally required at roof pitches less than 8 degrees combined with a self supporting paper. At roof pitches of 8° and above where non-self supporting paper is used or purlin spacing is in excess of self supporting criteria, netting or other support should be used. Alternative support to netting should be used in severe coastal environments including when aluminium is used.
- These details are for Roofing Industries profile/s as nominated and may not be applicable to other profiles.
- This drawing is the copyright of 'Roofing Industries' and can only be copied or reproduced with their permission.
- These details to be read with Roofing Industries profile technical summary regarding wind loads and fixings.
- Further information can be obtained from the NZ Metal Roof & Wall Cladding Code of Practice: www.metalroofing.org.nz OR NZBC clause E2/AS I.

Copyright detail (C) 201

