

Ezi-Lok™

Gutter Screen

Ezi-Lok™

Valley Screen

Innovative New Zealand developed spouting gutter and roof valley protection systems that are simple to install and remove!



What makes Ezi-Lok™ Gutter Screen and Ezi-Lok™ Valley Screen so unique?

It's a fact of nature that grime and seed is continually being deposited on your roof from weather and birds. This washes through most screens and into the gutters, ensuring a perfect growing medium for unsightly weeds.

Current systems tend to be permanently fixed in position and the only way to remove debris is to water blast through the mesh system, which is difficult, ineffective and rather messy to say the least.

Revolutionary Ezi-Lok™ Gutter Screen and Ezi-Lok™ Valley Screen systems on the other hand are simply snapped into or out of position allowing for easy access, ensuring simple cleaning with a garden hose.

Just look at the advantages:

- Simple to install and remove
- Manufactured from AR8™ Aluminium – no rust
- Leaves simply blow from the roof and are not deposited in the rainwater system
- Prevents birds or rats nesting in the roof
- Extremely attractive & complements the overall roof
- No need to perforate roofing with fasteners
- Simply installed after the roof is complete
- No more blocked downpipes
- No more clogged gutters or valleys
- Can be used on any roof type
- Available in a range of modern colours
- Low installation cost – DIY friendly

Roofing
Industries
roof.co.nz

Ezi-Lok™

Gutter Screen

Ezi-Lok™

Valley Screen



- Easy to install – suits most roofing types
- Attractive precoloured aluminium construction
- Simple to remove for easy gutter cleaning
- Can be manufactured to suit most spouting and gutters
- Excellent serviceable life and will not rust
- No need to drill through the roof
- Standard length 2 metres, maximum length 3 metres



- Easy to install – suits most roofing types
- Attractive precoloured aluminium construction
- Simply squeeze to insert or remove
- Excellent serviceable life and will not rust
- No need to drill through the roof
- Standard length 2 metres, maximum length 3 metres

Installing Ezi-Lok™ Gutter Screen




Diagram 1 - Position Leg "A" of the Ezi-Lok™ Gutter Screen into the gutter/spouting and up under the roof.






Diagram 2 - Compress the Ezi-Lok™ Gutter Screen slightly and push down the Ezi-Lok™ Gutter Screen edge "B" into the spouting/gutter beak.

Note: Although not a necessity, should you wish to join the Ezi-Lok™ Gutter Screen end laps together, use 8 x 20mm colour-matched square drive stitching screws, compatible with the aluminium and environment where installed. Each Ezi-Lok™ Gutter Screen length should be end lapped over the next section and if the home is dual level, ensure the laps face away from the normal roof view angle.



Installing Ezi-Lok™ Valley Screen

Gently squeeze the sides of the Ezi-Lok™ Valley Screen inwards and place in the valley tray. When in position release sides. The Ezi-Lok™ Valley Screen will spring open and lock into place. Where a change of angle is required, uniformly mitre both angles with snips and butt flush together. Where the lower end of the Ezi-Lok™ Valley Screen meets the Ezi-Lok™ Gutter Screen, gently bend down and mold the end so that it sits neatly on top of the Ezi-Lok™ Gutter Screen. This also prevents birds gaining access to the roof interior.



Note: Although not a necessity, should you wish to join the Ezi-Lok™ Valley Screen end laps together, use 8 x 20mm colour-matched square drive stitching screw compatible with the aluminium and environment where installed. Each Ezi-Lok™ Valley Screen length should be end lapped over the next section ensuring the laps face away from the normal roof view angle.



For metal longrun, concrete tile, and some higher rib metal tile roofing



For metal tile roofing

Authorised distributor/installer

Manufactured by:

