

SELECTION GUIDE

For inclusion on plan and as part of Full Specification Statement	
The (1)	profile shall be Eurostyle (1a)
The (1)	shall be (2)
The profile will be formed from Grade (3) _	
The gauge shall be (4)	
For prefinished / pre weathered material the system shall be (5)	
The colour is to be selected from the appropriate prefinished manufacturers colour chart.	
Ridging and hips shall be manufactured to match the roofing from the same material.	
All flashings shall be manufactured to match the roofing and/or cladding from the same material.	
Fixing methods and cover to all flashings are to meet the requirements of the Drawings, NZ Metal Roofing Code of Practice and/or NZBC E2/AS1 and Roofing Industries literature as appropriate.	
The underlay shall be Thermakraft (6)	
laid over plywood with a minimum recommended thickness of 15mm.	
Where necessary for expansion, use sliding clips as per the manufacturers recommendations.	
The roof/cladding fixing method shall be as per Roofing Industries Eurostyle Profile Technical Summary and is to suit a design	

wind load of _____ kPa to the body of the roof/cladding and _____ kPa to the periphery.

(Refer to Roofing Industries for Eurostyle Wall and Soffit Panel).



SELECTION GUIDE OPTIONS

- (1) Roofing
 - Cladding
 - Roofing and Cladding
- (1a) Double Standing Seam
 - Angle Seam
 - Roll Seam
 - Roll Cap
 - Snap Lock
- (2) Zincalume coated steel
 - Galvanised coated steel
 - Zam coated steel
 - prepainted steel
 - plain mill finish Aluminium
 - prepainted Aluminum
 - Copper
 - Titanium Zinc
 - Pre Finished Titanium Zinc
- (3) G300 (Steel)
 - 5052 ,H34 (Aluminium)
 - Alloy 122 (Copper)
 - as appropriate (Titanium Zinc)
- (4) .55mm BMT (Steel)
 - .70mm BMT (Aluminium)
 - .90mm BMT (Aluminium)
 - .55mm BMT (Copper)
 - .70mm BMT (Copper)
 - .70mm BMT (Titanium Zinc)
- (5) Colorcote ZR8 (Steel)
 - Colorcote ZRX (Steel)
 - Colorcote ZM8 (Steel)
 - Colorcote ZMX(Steel)
 - Colorsteel Endura (Steel)
 - Colorsteel Maxx (Steel)
 - Colorcote AR8 (Aluminium)
 - Colorcote ARX (Aluminium)
 - VM Pigmento Zinc
 - Titan Pigmento Zinc
 - VM Anthra Zinz
 - VM Quartz Zinc
 - VM Quartz Zinc Plus
 - Titan Zinc

- (6) 215 Self Supporting
 Covertek 407 Self Supporting Fire Retardent
- (7) Thermakraft Drainage Matt• Directly

EUROSTYLE

