EUROSTYLE SPANLOK® VARIABLE PAN(VP) **ROOFING ON PURLINS** TYPICAL CHANGE IN PITCH STOPEND TO PROFILE CHANGE IN PITCH FLASHING WITH UNDER FLASHING FIXED TO SUPPORTING PURLINS TO EVERY RIB UNDERFLASHING (2) -HEM TO FLASHING **ROOFING INDUSTRIES FDGF** EUROSTYLE SPANLOK® (4) **ROOF UNDERLAY FIXING STRIP WITH 3 FIXINGS** PER PAN FULLY SEALED IN BETWEEN SURFACES **ROOF FRAMING ROOF UNDERLAY STOPEND**

Detail Number: RI-ESVPRRPUR-050

Date drawn: 03/04/2025

Scale: 1:5@ A4

DETAIL ANNOTATION:

- SITUATION 1, 2 & 3 AS PER E2/AS1 TABLE 7
- HIGH TO EXTRA HIGH WIND ZONE DOUBLE FIX UNDERFLASHINGS
- 3. FASTENERS TO BE COMPATIBLE WITH MATERIAL BEING FIXED AND THE SUITABLE GRADE FOR THE ENVIRONMENT IN WHICH LOCATED
- CLIPS OMITTED FOR CLARITY

SITE WIND ZONE	X	MINIMUM
(As per NZS3604)	TRANSVERSE FLASHING OVER ROOFING	UPPER LAP UNDER ROOFING
SITUATION 1	130mm	250mm
SITUATION 2	200mm	250mm
SITUATION 3	NOT PERMITTED UNDER E2/AS1, REFER NZ METAL ROOF & WALL CLADDING CODE OF PRACTICE	

GENERAL NOTES:

- These details are to be read with Roofing Industries SPANLOK® Product Technical Statement and installation guide.
- These details are generally in compliance with E2/AS1 and/or the NZ Metal Roof & Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'.
- The building designer is ultimately responsible to ensure that details used meet the requirements of the NZ Building Code for the specific project.
- Details of the supporting structure including cavity battens are indicative only and are the responsibility of the building designer. For steel framed buildings thermal break cavity battens may be required.
- Roof/wall underlay selection are the responsibility of the designer. Underlay to be installed in accordance with underlay manufacturer's recommendations and requirements.
- These details are for Roofing Industries profile/s as nominated and may not be applicable to other profiles.
- This drawing is the copyright of 'Roofing Industries' and can only be copied or reproduced with their permission.
- Further information can be obtained from the NZ Metal Roof & Wall Cladding Code of Practice: www.metalroofing.org.nz or E2/AS1.
- Details are for steel based materials, other substrates may require some changes.
- All dimensions are nominal



UNDER FLASHING DETAIL
HEM TO BE CEAR OF
PAN 2-5mm





