EUROSTYLE ANGLE STANDING SEAM™ WALL CLADDING WINDOW / DOOR HEAD FLASHING FOR VERTICAL CLADDING ON CAVITY

ROOFING INDUSTRIES **EUROSTYLE ANGLE** SPANLOK™ CLIP STANDING SEAM™ SCRFW FIXED SECRET CLIP FIXED CASTELLATED CAVITY RIGID ROOFING BATTEN BETWEEN SUBSTRATE VERTICAL BATTENS ADDITIONAL BUILDING WRAP FROM OVERLAP ABOVE OR TOP PVC PERFORATED OF WALL LAPPED OVER FLASHING CAVITY CLOSURE OR USE WINDOW FLASHING TAPE BUILDING WRAP DRESSED INTO STOPEND TO PROFILE OPENING WITH 50mm RETURN TO INSIDE OF FRAME WITH WINDOW FLASHING TAPE INSTALLED OVER WRAP TO CORNERS 5mm nom 15 mm min cover I Omm STOP ENDS INCORPORATE LOmm 55 TURNUP AS STOP ENDS ROOFING INDUSTRIES HEAD FLASHING WITH AIR SEAL 15° FALL WINDOW PACKERS. FRAME

> (Dimensions are indicative only) Turn down end of head flashing to jamb flashing

GENERAL NOTES:

REFER TO E2/AS I FOR GENERAL WINDOW OPENING FOR WRAPPING OF FRAMED OPENING PRIOR TO WINDOW INSTALLATION.

Detail Number: RI-EASWO 12A

Date drawn: 02/02/2018

Scale: 1:5@ A4

- A MIN. OF 8mm EFFECTIVE COVER AT SILLS SHALL BE PERMITTED WHERE NECESSARY TO ALLOW FOR TOLERANCES.
- WINDOW PROFILE TO BE SELECTED TO ACHIEVE COVER SHOWN IN DETAILS
- ARCHITRAVE'S ARE SHOWN FOR CONSISTENCY ONLY. DETAIL MAY BE USED WITH REBATED LINER.
- 5. LIAISE WITH WINDOW MANUFACTURER PRIOR TO INSTALLATION
- ALLOW FOR SEPARATION FROM ANY CORROSIVE TIMBER TREATMENTS.
- 7 SFAL HEAD FLASHING TO WINDOW IN VERY HIGH & EXTRA HIGH WIND ZONES.
- 8 ALL DIMENSIONS SHOWN ON DRAWINGS ARE NOMINAL +/- 5mm
- CASTELLATED TIMBER BATTEN OR APPROVED DRAINED BATTEN MAY BE USED WITH THIS SYSTEM.

REFERENCE FLASHINGS: NZ METAL ROOF AND WALL CLADDING CODE OF PRACTICE. E2/AS I OR REFER MANUF DETAILING. DIMENSIONS ARE INDICATIVE ONLY

Copyright detail (C) 2017





- These details are generally in compliance the NZ Metal Roof \$ Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'. Eurostyle falls outsider the criteria of E2/ASI and this document is therefore not applicable.
- The building designer is ultimately responsible to ensure that details used meet the requirements of the NZ Building Code for the specific project.
- Details of the supporting structure including cavity battens are indicative only and are the responsibility of the building designer. For steel framed buildings thermal break cavity battens may be required.
- Underlay selection and building wrap types are the responsibility of the designer.
- These details are for Roofing Industries profile/s as nominated and may not be applicable to other profiles.
- This drawing is the copyright of 'Roofing Industries' and can only be copied or reproduced with their permission.
- These details to be read with Roofing Industries profile technical summary regarding wind loads and fixings.
 - Further information can be obtained from the NZ Metal Roof \$ Wall Cladding Code of Practice: www.metalroofing.org.nz or E2/AS I.

