
AURA ROOFING ON STEEL FRAMING
RAINWATER HEAD

Detail Number: RI-CAR-050A
Date drawn: 13/10/2026
Scale: 1 : 5@ A4




DIMENSION Y EQUAL TO DEPTH OF GUTTER AT OUTFLOW

DIMENSION X EQUAL TO OR GREATER THAN WIDTH OF GUTTER PLUS 3mm

DIMENSION Z GREATER THAN OR EQUAL TO 25mm

CROSS-SECTION AREA OF OVERFLOW GREATER THAN OR EQUAL TO CROSS-SECTION AREA OF OUTLET



GENERAL NOTES:

- These details to be read with Roofing Industries AURA Product Technical Statement and Installation Guide.
- The building designer is ultimately responsible to ensure that the details used meet the requirements of the NZ Building Code for the specific project.
- Details of the supporting structure (including cavity battens if used) are indicative only and are the responsibility of the building designer. For steel framed buildings thermal break cavity battens may be required.
- Roof/wall underlay selection are the responsibility of the designer. Underlay to be installed in accordance with underlay manufacturer's recommendations and requirements.
- These details are for Roofing Industries profile/s as nominated and may not be applicable to other profiles.
- This drawing is the copyright of 'Roofing Industries' and can only be copied or reproduced with their permission.
- Further information can be obtained from the NZ Metal Roof & Wall Cladding Code of Practice: www.metalroofing.org.nz or E2/AS1 where applicable.
- Details are for steel-based materials, other substrates may require some changes.
- All dimensions are nominal.
- Fixing: The designer needs to check the screw manufacturers technical data of the selected screw type for the design wind load and the material being fastened to.

Copyright detail © 2026

Roofing Industries
roof.co.nz