




Green Tick Acrylic



Green  Tick Acrylic® cast sheet is a recent proprietary development in specialty acrylics, utilising innovative technology by incorporating both recycled & virgin raw materials, into a premium quality finished product.

Green  Tick Acrylic® is enabling a new generation of sustainable acrylic production, creating an environmentally friendly option with the goal of assisting the protection of our planet.


Features



- Specially formulated proprietary technology.
- Excellent light transmission & optical clarity.
- Perfect cast acrylic finish (no manufacturing lines & inclusions).
- Good mechanical properties; shatter resistant

Applications

- Picture framing
- POP Displays
- Exhibit displays
- Signage & displays
- Poster advertising protection

COLOUR RANGE *(May not represent the physical product)*



Green  Tick Acrylic® is the registered trademark of the product manufacturer. Green  Tick Acrylic® is not associated with any product certification services.

PRODUCT RANGE/DIMENSIONS		
Type	Thickness	Length & Width
Clear	2.0mm	2440mm x 1220mm
	2.5mm	
	3.0mm	
	4.5mm	
	6.0mm	
White Opal Black	3.0mm	2440mm x 1220mm
	4.5mm	
	6.0mm	
	10.0mm	

PANEL PHYSICAL PROPERTIES	
Type	Result
Density	1.19g/cm ³
Weight (3.0mm)	3.69kg/m ²
Gauge Tolerance	+/- 2%
Light Transmission	91% (Clear)
Service Temperature	70°C
Vicat Softening Temperature	100°C
Forming Temperature	140°C - 150°C
Minimum Cold Bending Radius	210 times the sheet thickness
Expansion/ Contraction Rate	5.0mm/m
Fire Rating	Group 4
Cleaning	PSP Cleaner or warm soapy water & soft cloth.

NOTE: Uncontrolled in printed format.