



Multiboard



Multiboard Integral Foam PVC is a lightweight, extruded, rigid foam PVC with a hard surface finish on both sides.

Available in a range of thicknesses Multiboard is also waterproof with good UV stability which makes the product idea in the signage, construction & Joinery markets.

Features

- Fine cell structure
- Hard surface finish
- Lightweight
- Waterproof
- Non corrosive
- Good UV stability
- Chemical resistant
- Low flammability
- Good thermal insulation
- Excellent printability
- Easy to fabricate, similar to wood

Applications

- Signage & displays
- Boat building
- Exhibition stands
- Construction
- Industrial applications
- Kitchen & bathroom joinery

COLOUR RANGE *(May not represent the physical product)*



| PRODUCT RANGE/DIMENSIONS | | |
|--------------------------|-----------|-----------------|
| Profile/Colour | Thickness | Length & Width |
| White Semi-Gloss | 10.0mm | 2440mm x 1220mm |
| | 12.0mm | |
| | 16.0mm | |
| | 18.0mm | |
| | 20.0mm | |
| | 30.0mm | |
| White Semi-Gloss | 10.0mm | 3000mm x 1220mm |
| | 20.0mm | |

| PANEL PHYSICAL PROPERTIES | |
|-----------------------------|--|
| Type | Result |
| Density | 55g/cc (10.0mm & 16.0mm) 60g/cc (20.0mm & 25.0mm) |
| Weight (10mm) | 5.23kg/m ² |
| Gauge Tolerance | +/- 0.3mm - 0.5mm |
| Service Temperature | -10°C - +55°C |
| Vicat Softening Temperature | 75°C |
| Heat Deflection Temperature | 63°C |
| Expansion/Contraction Rate | 0.08.0mm/m |

NOTE: Uncontrolled in printed format.