

DUMAWALL+ WATERPROOF WALL TILES



PURPOSE

PSP Ltd supplies Dumawall+ Waterproof Wall Tiles for use as a waterproof interior surface finish.

EXPLANATION

Dumawall+ Waterproof Wall Tiles are 5 mm thick uPVC tiles, with an interlocking tongue and groove profile on all four edges. The tiles are installed using adhesive. Dumawall+ Waterproof Wall Tiles are available in the following sizes:

- 375 mm x 650 mm (ex-stock)
- 375 mm x 1200 mm (indent)
- 500 mm x 900 mm (indent)
- 500 mm x 1200 mm (indent)

PSP provides the following Dumawall Aluminium trims:

- finishing trim
- click finishing trim
- universal corner 12-20 mm
- inside corner 12 mm
- L-trim outside corner 16-12 mm
- start trim.



For further assistance please contact:

- ☎ 0800 786 883
- ✉ info@psp.co.nz
- 🌐 www.dumawall.co.nz

SCOPE AND LIMITATIONS OF USE

Scope	Limitations
Building On any internal wall panel substrate that complies with the NZ Building Code or where the designer and/or installer have established that the substrate is suitable for the intended building work.	<ul style="list-style-type: none"> ➤ In buildings where material group number 3 or greater is permitted. ➤ Dumawall+ Waterproof Wall Tiles must not be installed behind heat sources such as hobs. ➤ The adhesive must be Dumafix PVC glue or SikaFlex 123 MS.



USEFUL INFORMATION

For design, installation, maintenance and warranty information for Dumawall+ Waterproof Wall Tiles, and for supply and manufacturing information, and the statement made about s26 of the Building Act 2004, refer to www.dumawall.co.nz

PERFORMANCE CLAIMS

If designed, installed and maintained in accordance with all PSP Ltd requirements, Dumawall+ Waterproof Wall Tiles will comply with or contribute to compliance with the following performance claims:


NZ Building Code clauses	BASIS OF COMPLIANCE	
	Compliance statement	Demonstrated by
B1 Structure B1.3.1 B1.3.2 B1.3.3 (a, j, q)	ALTERNATIVE SOLUTION	➤ CE certification of manufacture to EN 13245-2:2008 Plastics. Unplasticized poly(vinyl chloride) (PVC-U) profiles for building applications, PVC-U profiles and PVC-UE profiles for internal and external wall and ceiling finishes [Dumaplast NV, 11/03/2022].
B2 Durability B2.3.1 (b) B2.3.1 (c)	ALTERNATIVE SOLUTION	➤ CE certification of manufacture to EN 13245-2:2008 Plastics. Unplasticized poly(vinyl chloride) (PVC-U) profiles for building applications, PVC-U profiles and PVC-UE profiles for internal and external wall and ceiling finishes [Dumaplast NV, 11/03/2022].
C3 Fire affecting areas beyond the source C3.4 (a)	ACCEPTABLE SOLUTION C/AS1 and C/AS2	➤ Classified by Crepim testing laboratory as D-s3, d0/DHG in accordance with EN 13501-1, equivalent to Material Group 3 [Dumaplast NV, 11/03/2022].
E3 Internal Moisture E3.3.4 E3.3.5 E3.3.6	ALTERNATIVE SOLUTION	➤ CE certification of manufacture to EN 13245-2:2008 Plastics. Unplasticized poly(vinyl chloride) (PVC-U) profiles for building applications, PVC-U profiles and PVC-UE profiles for internal and external wall and ceiling finishes [Dumaplast NV, 11/03/2022].
F2 Hazardous Building Materials F2.3.1	ALTERNATIVE SOLUTION	➤ Tested by Eurofins for VOC emissions and formaldehyde release to EN 16516:2017, ISO 16000 (parts 3, 6, 9, 11) 2006- 2011 depending on part, and EN717-1:2004; Eurofins accredited for testing [Eurofins, 7/08/2018].

SOURCES OF INFORMATION

- Dumaplast NV. [11/03/2022] *Declaration of performance DOP-CPR-6.*
- Eurofins. [7/08/2018] *VOC Emission Test Report.*

SCAN OR CLICK THIS QR CODE
FOR A FULL DOWNLOAD OF
COMPLIANCE DOCUMENTATION
FOR THIS PASS™.

www.dumawall.co.nz



1. Where a standard is referenced it is to be read as amended by the acceptable solution or verification method as applicable.
2. Sources of information also include the Building Act 2004 and its regulations, including the Building Code (Schedule 1 of the Building Regulations 1992), Acceptable Solutions and Verification Methods, and relevant cited standards.
3. The quality and assurance that the supplied products meet the performance claims stated in this pass™ are the responsibility of the company that is the holder of this pass™.
4. The availability of the information about the supplied products required to be disclosed under s14G(3) is the responsibility of the company that is the holder of this pass™.

PSP Ltd confirms that if Dumawall+ Waterproof Wall Tiles is used in accordance with the requirements of this pass™ the product will comply with the NZ Building Code and other performance claims set out in this pass™ and the company has met all of its obligations under s14G(2) of the Building Act.

Date of first issue: 23/07/2019

Date of current issue: 17/07/2023

NZBN: 9429038193958

Kevin Brunton

Kevin Brunton, Technical Director, TBB confirms that the process used to prepare this pass™ on behalf of PSP Ltd has been undertaken in accordance with MBIE PTS guidelines and in accordance with the TBB pass™ process which is within the scope of TBB's ISO 9001 certification.

9606D66ADE51EA6CCC25850D00239F99