



Viking Peel & Stick Membrane

Product Information

Applications

Viking Peel & Stick Membrane is a self adhesive damp-proof membrane (DPM) for vertical and horizontal waterproofing applications. It has been BRANZ Appraised (No. 826) as a DPM for use under floor slabs; behind masonry walls and on substrates of insitu or pre cast concrete.

Physical Description

The Viking Peel & Stick system comprises of a 1.5mm thick rubberised asphalt membrane, on the face of which a heavy duty, high impact polyethylene film is laminated. The adhesive side has a removable release sheet which is peeled back at the time of application to the substrate.

Code	Roll Dimensions	Weight	Colour
SEE015	1.5mm x 0.914m x 20.4m	37kg (2kg/m ²)	Dark Grey
SES301	19L Bituminous Primer	18kg/pail	N/A

Physical Property

Property	Test method	Test Results
Colour	-	Black
Tensile (Membrane)	ASTM D415	325 psi
Tensile (Film)	ASTM D882	5, 000 psi
Elongation	ASTM D412	350%
Permeance	ASTM E96	0.05 perms
Low Temp. Flexibility (100 Cycles)	ASTM D1970 ASTM C836	Unaffected, @ 45° F Cracking Cycle* Unaffected @ -25° F
Peel Strength	ASTM D903	10lb / in
Lap Adhesion	ASTM D1876	19.0 lb/in
Puncture Resistance	ASTM E154	60 lb min
Soil Burial	GSA-PBS 07121	16 wks, no effect
H2O Absorption	ASTM D570	0.1% by wt
Hydrostatic Head	ASTM D751	230 ft

* 180° bend over a 1" (25mm) mandrel at -45° F (-43°C)