

## Product Overview

Complies with E2 as an Alternative Solution. BRANZ Appraised - Certificate No. 864



BRANZ Appraised  
Appraisal No. 864 [2016]

masterspec  
Ref No. 4421 SB

# Viking General Membrane Mercury FC Below-Ground DPM Torch-on Membrane

## Technical Statement

### Product Description

The Viking Mercury FC Membrane is a modified-bitumen, torch-on, damp-proof membrane (DPM) waterproofing system for vertical and horizontal tanking applications. It is primarily applied to the outside of a sub-structure of a building (such as a foundation or basement) to prevent water ingress.

Other forms of tanking where Mercury FC can be used include under floor slabs, behind masonry walls, the lining of substrates of in situ or precast concrete; retaining walls, cellars, lift shafts, tunnels, plaza decks, roof gardens and planter boxes.

Viking Mercury FC comprises of a 4mm thick reinforced-polyester and fibreglass SBS (Styrene butadiene styrene) modified-bitumen membrane which is torch-applied for maximum adhesion to a compatibly primed surface. The inherent reinforcement in the sheet maximises the tensile strength necessary to deal with latitudinal movement of the substrate. The Mercury FC system consists of the membrane, bituminous primer, bituminous gum, protection boards and drainage boards, Mercury FC has a cold flexibility down to -20 degrees Celsius. Being 4mm thick, it possesses very high puncture resistance as well as very high chemical resistance. Mercury FC resists hydrostatic pressure and is mechanically strong.

Mercury FC comes in rolls 4mm thick x 1.0m wide x 10m long. It is BRANZ Appraised No.864 (2016) and holds a 20-year product warranty. Viking Roofspec is an active member of the Waterproofing Membrane Association Inc. (W.M.A.I.); an incorporation of companies whose goal is to lift the standard of waterproofing in New Zealand.

The W.M.A.I. is formulating a "Tanking Code of Practice" for the Department of Building and Housing.

### Scope of use

Viking Mercury FC DPM Membrane has been appraised as a DPM for use:

- On buildings subject to non-specific design under floor slabs complying with NZS 3604 and behind concrete masonry basement walls and under floor slabs complying with NZS 4229; and,
- On buildings subject to specific design with substrates of in situ or precast concrete complying with NZS 3101 or concrete masonry complying with NZS 4230; and, Where subsoil drainage and free draining granular backfill has been placed behind basement walls.

Viking Mercury FC DPM Membranes must be adequately protected against damage during backfill and in service.

## New Zealand Building Code (NZBC)

The product will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- Clause B1 Structure: Performance B1.3.1
- Clause B2 Durability: Performance B2.3.1, B2.3.1(a), B2.3.2, B2.3.2(a)
- Clause E2 External moisture: Performance E2.3.3
- Clause F2 Hazardous building materials: Performance F2.3.1

## Supporting Evidence

The product has and can make available, the following additional evidence to support the above statements:

### Product Criteria

#### Design requirements

Product specification and incorporation of Viking Mercury FC Membranes into the building design shall be carried out by a designer/architect/engineer or a building professional who:

- Is qualified to design the buildings covered under the 'Scope' of use of this product.
- Has ready access to the technical specifications including installation details and standards referenced in the BRANZ Appraisal No. 864 (2016) where the design limitations are outlined for the scope of this PTS.

Accessories in the Viking Mercury FC system include bituminous primer (20L), bituminous gum, protection boards and drainage boards.

#### Installation requirements

- Installation shall be carried out by a Viking Roofspec trained and licensed installer.
- Installation shall be undertaken in accordance with all relevant technical information related to the selected installation method, including information contained within the BRANZ Appraisal No. 864 (2016).

#### Maintenance requirements

- Annual inspections must be made of the membrane's top edge seal and protection, the backfill capping, and the drainage pipe to ensure all are functioning as originally designed.
- If required, the drainage pipe must be cleared to remove any sediment or silt build-up.  
The slope of the backfill capping must be maintained at all times.
- Long term properties of the material may be affected by contact with petroleum-based products such as oils, greases and solvents.

#### Warranties

The Viking Mercury FC system is backed by a 20-year product warranty.

## Company Product Information

### Environmental

Bitumen is a bi-product of the oil refining process. Torch-on membranes provide a constructive use of this waste product. The robust nature of a modified bitumen membrane system will ensure sustainability through longevity.

# masterspec

Visit [nextgen](#) or [masterspec](#) for the online version of our specification.

### CAD Details

Please visit our website [www.vikingroofspec.co.nz](http://www.vikingroofspec.co.nz) or our masterspec listing for our latest CAD Roofing details.

### Viking Mercury FC Physical Properties

Mercury FC		
Property	Test Method	Test Results
Watertightness (metodo B)	EN 1928:2000	Pass
External fire performance	EN 1350-5	F roof
Reaction to fire	EN 13501-1	EUROCLASSE F
Shear resistance of joint - heat lap - side lap	EN 12317-1	650 400
Tensile properties - maximum longitudinal tensile strength - maximum transversal tensile strength - longitudinal elongation - transversal elongation		750 N/50 mm 500 N/50 mm 35% 40%
Resistance to impact	EN 12691	1000 mm
Resistance to static loading	EN 12730	15 kg
Resistance to tearing (nail shank) - longitudinal - Transversal	EN 12310-1	140 N 140 N
Dimensional stability	EN 1107-1	0.5%
Flexibility at low temperature	EN 1109	-20°C
Flow resistance at elevated temperature	EN 1110	120°C
Artificial ageing by long term exposure to elevated temperature	EN 1269 + EN 1110	110°C
Water vapour transmission properties		$\mu=20.000$



# Viking Mercury FC Membrane System Product Warranty

Viking Roofspec offers this Warranty for the Viking Membrane System for 20 years from the Warranty Commencement Date ("Warranty Period").

1. Viking Roofspec warrants that the Membrane System will, subject to the terms set out below, retain its waterproofing for the Warranty Period provided that the Membrane System has been properly installed by a Viking Approved Applicator in accordance with all Viking Roofspec specifications current at the time of installation, including, but not restricted to the technical data and standard details as listed on the Viking Roofspec Website at [www.vikingroofspec.co.nz](http://www.vikingroofspec.co.nz) and training provided by Viking Roofspec ("Viking Specifications").
2. This Warranty covers only materials supplied by Viking Roofspec as the Membrane System, including the membrane and primer provided materials were new and unused at the time of installation and have not been disturbed thereafter.
3. Warranty Commencement Date \_\_\_\_\_  
(Date of completion of Membrane System installation)
4. The Membrane System  
Membrane type: Viking Mercury FC
5. The Building  
Project address \_\_\_\_\_  
Tanking application \_\_\_\_\_  
Installed by \_\_\_\_\_
6. This Warranty covers only the waterproofing properties of the Membrane System. Viking Roofspec will not be liable for any failure of the Membrane System or damage resulting from any failure that has been caused in part or in whole by the Membrane System not being installed in accordance with the Viking Specifications. Viking Roofspec does not give any warranty as to the suitability of any installer and will not, in any circumstances be liable for the actions or omission of any installer. Viking Roofspec requires that all Viking Approved Applicators provide a separate Workmanship Warranty covering any defects in the installation of the Membrane System.
7. The Membrane System is not warranted against, and Viking Roofspec shall not be liable for loss of waterproofing properties or damage caused by:
  - objects penetrating the sheeting, or mechanical damage;
  - chemical or substance;
  - any shifting or altering of the building after installation;
  - the failure of other Building components;
  - the lack of adequate protection for the membrane
  - the lack of adequate drainage;
  - environmental factors including pollutants and biological agents, contaminated water or contaminated earth;
  - accident or intentional or negligent acts, misuse, abuse, vandalism or civil disobedience or the like; or
  - Acts of God which include, but are not limited to, acts of nature without human intervention, such as earthquakes, storms, floods, and explosions.

**Auckland Office**  
80 Alexander Crescent, Otara  
PO Box 14-541, Panmure  
Auckland 1741, New Zealand

**Christchurch Office**  
2 Nazareth Avenue, Middleton  
PO Box 9117, Tower Junction  
Christchurch 8149, New Zealand

**T.** 0800 729 799  
**F.** 0800 729 788  
[info@vikingroofspec.co.nz](mailto:info@vikingroofspec.co.nz)  
[www.vikingroofspec.co.nz](http://www.vikingroofspec.co.nz)

**Viking** Roofspec  
Taking care of detail

8. In addition to the above limitations, this Warranty will be void and Viking Roofspec will not be liable under it if;
  - any alteration or repair is made on or through the Membrane System (including, but not limited to: structures, fixtures or utilities) without prior written authorisation from Viking Roofspec;
  - any alteration or repair is made to the Membrane System by a person other than a Viking Approved Applicator;
9. Viking Roofspec shall not be liable under this Warranty (or any implied warranties which are not excluded under clause (15) for any consequential, indirect or special loss or damage of any kind whatsoever, or loss of profits, whether under contract, tort or otherwise.
10. Viking Roofspec's liability is in any circumstances limited to (at the option of Viking Roofspec) either;
  - providing for the repair of the original Membrane System,
  - or providing a credit to be applied towards the purchase of a new Membrane System, calculated *pro rata*, based upon the number of remaining months of the unexpired Warranty Period, using the current material prices for the Membrane System. The maximum *pro rata* value allowed by Viking Roofspec for repair or credit shall not exceed the original purchase price of the product supplied.
11. The obligations under this Warranty shall only be enforceable against Viking Roofspec upon completion of the installation of the Membrane System; completion of the installation contract; and once payment in full has been received for the product supplied.
12. Should any defect occur which requires a remedy under the terms of this Warranty, then the defect must be notified to Viking Roofspec in writing within fourteen (14) days of discovery. By notifying Viking Roofspec you authorise Viking Roofspec to investigate the Warranty claim to assess whether it falls within the terms of this Warranty. Should our investigation of the claim find that the cause is outside the terms of this Warranty, then you acknowledge and agree that Viking Roofspec may charge you its reasonable investigation costs. You agree to provide Viking Roofspec free access to the Membrane System in order to investigate or to affect repairs under this Warranty during normal business hours.
13. Any remedial work required under this Warranty shall be as determined by Viking Roofspec and shall be carried out in accordance with the Viking Specifications by a contractor nominated by Viking Roofspec. Viking Roofspec does not accept liability for delay in sourcing repair materials.
14. Nothing in this Warranty shall require Viking Roofspec to shift any earth, hardfill, structure fixtures, plant, equipment, flashings or other items so as to allow access to part of any Membrane System to be repaired or replaced. Neither shall Viking Roofspec be liable for any costs involved in such shifting or reinstallation.
15. This Warranty represents the limit of Viking Roofspec's liability for the Membrane System. All other warranties, express or implied, are hereby excluded to the maximum extent permitted by applicable law.
16. Notwithstanding any other provisions of this Warranty, nothing in this Warranty is intended to limit any condition, warranty, right or remedy available under or imposed by any applicable legislation including, for the avoidance of doubt but without limitation, the Building Act 2004, the Fair Trading Act 1986 and the Consumer Guarantees Act 1993) except to the extent permitted by such legislation.



**Auckland Office**  
80 Alexander Crescent, Otara  
PO Box 14-541, Panmure  
Auckland 1741, New Zealand

**Christchurch Office**  
2 Nazareth Avenue, Middleton  
PO Box 9117, Tower Junction  
Christchurch 8149, New Zealand

**T.** 0800 729 799  
**F.** 0800 729 788  
info@vikingroofspec.co.nz  
www.vikingroofspec.co.nz



17. This Warranty shall be governed according to the laws of New Zealand and any disputes shall be decided in the courts of New Zealand.

\_\_\_\_\_  
Warranty Workmanship no

\_\_\_\_\_  
Viking Warranty No

\_\_\_\_\_  
For Viking Roofspect

\_\_\_\_\_  
Date issued



**Auckland Office**  
80 Alexander Crescent, Otara  
PO Box 14-541, Panmure  
Auckland 1741, New Zealand

**Christchurch Office**  
2 Nazareth Avenue, Middleton  
PO Box 9117, Tower Junction  
Christchurch 8149, New Zealand

**T.** 0800 729 799  
**F.** 0800 729 788  
info@vikingroofspect.co.nz  
www.vikingroofspect.co.nz

