





## HOME GETS A MAKEOVER – PAKURANGA, AUCKLAND

CHALLENGE: THE SUTTON
RESIDENCE OF PAKURANGA
IN AUCKLAND, WAS IN NEED
OF A TOTAL REFURBISHMENT
WHICH WOULD INCLUDE AN
ADDITION TO THE EASTERN
END OF THE HOUSE.

Initially, the house's 41 year-old pitched steel roof was going to be freshened-up with two coats of paint, however faint water stains on some areas of the internal ceilings pointed to some water ingress. From the outside, the roof also looked to be 'dipping' in areas, indicating that the purlins needed some re-work as well. The addition's new roof would also have looked slightly different next to the freshly-painted old one. So the decision was made to fully

replace the original steel roof (approximately 180m2 including slope) with a new watertight one that had a fresh modern look to match the roof of the addition (80m2 including slope), and therefore visually tie the old and new buildings together. The decision to make a full replacement rendered the opportunity for the Suttons to change the roofing genre altogether if desired. But to which genre?

## Solution

The Suttons preferred tiles or shingles to sheetmetal. The decision was relatively easy for them. They decided on a CertainTeed asphalt shingle roof for the following reasons:

- Aesthetics 1 Asphalt shingles looked smarter to them than other types of roofing.
- Aesthetics 2 Asphalt shingles suited their house's architecture.
- Bracing The new plywood substrate braced the entire roof.
- BRANZ CertainTeed shingles are BRANZ appraised.
- Light-weight asphalt shingles on ply weigh less than 20kg/m2 versus concrete or clay tiles which go up to 45kg/m2.

- Quality Installation Only Viking Roofspec Approved Applicators are trained to install them.
- Warranty CertainTeed's 'Landmark' profile comes with a 30 year product warranty.
- The CertainTeed system had a superior ridge ventilation system to any other.
- Value for money The 'Landmark' shingle profile (including plywood and installation) priced within only \$10.00 to \$15.00 / m2 of the other 'mainstream' genres such as concrete, clay and decramastic tiles.

So in the Spring of 2011, a Viking Roofspec Approved Applicator was commissioned by the Suttons to install their new roof. Accordingly, the old metal roof was removed and some of the old timber purlins were either replaced, packed-up, or buzzed-down to correct

potential sagging of the plywood when installed on top.

Before installing the plywood, ease of access to the ceiling also allowed for new insulation Batts to be installed. The applicator then spent significant time with the building contractor ensuring that the levels of the new building's roof trusses would line up nicely with the existing so that the roof transition would happen seamlessly.

Once the plywood was installed, CertainTeed's 'Landmark' profile shingles in the 'Moire Black' colour were nailed to it according to Viking

Roofspec's specifications. The whole process took approximately 5 working days for 3 installers.

**Auckland Office** 

80 Alexander Crescent, Otara PO Box 14-541, Panmure Auckland 1741, New Zealand Christchurch Office 2 Nazareth Avenue, Middleton PO Box 9117, Tower Junction Christchurch 8149, New Zealand T. 0800 729 799 F. 0800 729 788 info@vikingroofspec.co.nz www.vikingroofspec.co.nz









## Result

The Suttons are thrilled with the incredible aesthetic transformation the CertainTeed asphalt shingle roof has made. They're particularly thrilled with the way the shingles have visually tied the new extension to the old house.

They've also gained satisfaction and peaceof-mind from the beefed-up insulation in the ceiling; re-worked purlins; and the extra bracing provided by the staggered, 15mm tongue-andgroove eco-ply sheets nailed at 150mm centres to the purlins.

Lastly, they know that in the unlikely event of any issues with the performance of the shingles, Viking Roofspec (financially backed by the Tiri Group) and in-turn the manufacturer CertainTeed, will back them for the 30 year period of the warranty.

## How was the roof constructed?

- ShingleVent II ®
   Installed under Viking CertainTeed ridge cap
- 2. Viking CertainTeed Shingles
- 3. 15w Saturated Felt Underlay
- 4. Plywood Substrate











