

Dulux AcraTex Tiltwash 400/4

NZDA1094

Part A	194-85773
--------	-----------

Product Overview

DULUX AcraTex 400/4 Tilt Wash is a water based low toxicity cleansing solution designed specifically to remove bondbreakers from concrete panels prior to the application of a paint/texture system.

Features And Benefits

- | | |
|--|--|
| <ul style="list-style-type: none"> Water based Removes Bondbreakers Spray application Fast removal of bondbreakers | <ul style="list-style-type: none"> Easy application, clean up Cleans and conditions the concrete removing any stubborn contaminants. May be applied by airless spray which greatly reduces time on site. Uses approximately 1/5 of water vs high pressure water blaster method |
|--|--|



Uses And Typical Specifications

Uses	DULUX AcraTex 400/4 Tilt Wash is designed to be applied over Tilt Up or Off Form concrete panels that have been treated with a bondbreaker or release agents prior to painting or texturing to ensure maximum adhesion of the subsequent coatings. It is designed to be sprayed onto the substrate then quickly washed off with water.
-------------	--

Performance Guide

Weather	Not applicable	Salt	Not applicable
Heat Resistance	Not applicable	Water	Not applicable
Solvent	Not applicable	Abrasion	Not applicable
Acid	Not applicable	Alkali	Not applicable

Typical Properties

V.O.C Content	0	Clean Up	Clean up water																								
Application Method	  Air Spray Airless Spray Other: Garden pressure atomiser																										
Application Conditions	<table border="1"> <thead> <tr> <th></th> <th>Min</th> <th>Max</th> <th>Recommended</th> </tr> </thead> <tbody> <tr> <td>Solids By Volume</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>Recoat Time (min)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table>				Min	Max	Recommended	Solids By Volume	1			Wet Film Per Coat (microns)	0	0	0	Dry Film Per Coat (microns)	0	0	0	Recoat Time (min)				Theoretical Spread Rate (m²/L)	7	7	7
	Min	Max	Recommended																								
Solids By Volume	1																										
Wet Film Per Coat (microns)	0	0	0																								
Dry Film Per Coat (microns)	0	0	0																								
Recoat Time (min)																											
Theoretical Spread Rate (m²/L)	7	7	7																								

Application Guide

<p>Surface Preparation</p>	<ul style="list-style-type: none"> • TESTING FOR BONDBREAKER <p>Firstly identify the bondbreaker used on your project, this may be as simple as asking the foreman/builder of the project. The builder or a subcontractor usually constructs tilt panels. There may still be a drum present on site.</p> <p>The bondbreaker will either be water or solvent-based.</p> <p>1: WATER-BEAD TEST Spraying the panel with water and observing a beading of the water as it is sprayed onto the panel (just like water on a freshly waxed car). This indicates the presence of bondbreaker. If the panel does not bead, the concrete should take on a darker appearance. This is where the water has absorbed into the panel, if this happens perform the second bondbreaker test.</p> <p>2: pH INDICATOR TEST Fill a small spray bottle with clean water. Immerse a pH indicator strip* into the water to test the pH level. This should read 6.5-7.5. If it reads any higher the water may be contaminated. Try sourcing water directly from tap. Hold a fresh indicator strip on the concrete panel keeping the indicator pads in contact with the concrete at all times. Spray the tested water above the strip so that the water trickles down over the indicator strip. Let soak for approximately 1 minute. Align the indicator strip with the coloured scale on the packet and read the pH level of your concrete. If the reading is the same or very similar to your previous reading of clean water, you know there is still bondbreaker on the panel. If the reading is high (8+) the pH is being read directly from the panel meaning there is no bondbreaker present.</p>
<p>Application Procedure And Equipment</p>	<ul style="list-style-type: none"> • A sample area should be trialled first then checked for the presence of bondbreaker. • Suitable substrates: Tilt Up/ Off Form Concrete/ Pre Cast Concrete • Commence application, working from bottom of panel upward. <p>Apply using an airless spray unit (eg Graco 695 with a .0015 - .0019 tip at 1000 psi) or a low pressure knapsack spray unit.</p> <p>Large panels should be articulated into manageable work areas, always maintaining a wet edge ensuring rinsing of TiltWash is actioned prior to the area drying. If TiltWash dries, re-apply TiltWash to the affected area and rinse thoroughly.</p> <p>Flood the area with an excess of material with a heavy spray rather than a thin jet or light mist. This will produce a foaming wave of excess material descending down the panel.</p> <p>As TiltWash is applied the panel should take on a darkened appearance. Should this not happen, apply a second coat of TiltWash and consult with Dulux AcraTex if the panel does not darken (excessively applied water based bondbreaker may be the cause).</p> <p>NOTES:</p> <ol style="list-style-type: none"> 1. Chemical goggles, gloves and a mask should be worn at all times whilst pouring and applying TiltWash. 2. Application of TiltWash should be with an airless spray unit or low pressure knapsack spray only. 3. Application of TiltWash on large panels is a 2-man procedure, one to apply TiltWash the other rinsing with water. Never allow TiltWash to dry before rinsing. <p>RINSING TILTWASH</p> <p>Rinse panel with a flood of water (heavy spray not jet) deluging panel from top to bottom. Ensure extra care is taken whilst rinsing to ledges, sills and all fixtures on panels. A second rinse should be performed whilst panel is still wet from initial rinse. This is to make sure all remnants of bondbreaker and TiltWash are removed.</p> <p>This product should not be released into any watercourses, drains or gutters neat or diluted and should be contained and disposed of under local waste management procedures. An environmental duty of care must be executed at all times whilst using this product.</p> <p>NOTES:</p> <ol style="list-style-type: none"> 1. Do not wait until TiltWash is drying on panel before rinsing. Rinsing must occur whilst TiltWash is still wet and active to remove all traces of bondbreaker and TiltWash. 2. Water pressure should be at least 80 psi or 28kpa. 3. A second rinse is imperative to the performance of TiltWash. <p>PRIOR TO PAINTING</p> <p>Cross-hatch adhesion and pH tests must be performed as per Australian Standard AS2311-Painting Buildings and AS1580-Methods of Testing Adhesion (current editions) prior to commencing full-scale works. pH readings must be below 10 before coatings can be applied.</p> <ul style="list-style-type: none"> • Garden pressure atomiser/airless spray

Health And Safety			
MSDS Number	10858	Using Safety Precautions	Avoid any skin contact and inhaling spray mist. Use in well ventilated areas. Always use overalls, safety shoes, safety mask or respirator, safety glasses and safety gloves. For detailed information refer to product Material Safety Data Sheet available through Dulux Sales and Customer Service offices.
MSDS Link	http://msds.duluxgroup.com/pdf/shess-en-cds-020-000000010858.pdf		
Protective Equipment	Always use overalls, safety shoes, safety mask or respirator, safety glasses and safety gloves.	Storage	Store in cool place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.
Disposal	Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.	Handling	Avoid any skin contact and inhaling spray mist. Use in well ventilated areas.
In the case of emergency, please call 0800 734 607			

Precautions And Limitations
Recommendations, permissible coverage rates & application temperature must be observed.
Never allow TiltWash to dry before rinsing.

Transport And Storage			
Pack A	194-85773	Shipment Name	Not dangerous goods; No special transport requirements
Size	15 Litre	Weight	16 Kg
Flash Point	NA	UN Number	NA
Dangerous Goods Class	NA	Package Group	NA

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "AcraTex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118