

SC Core Doorset

DESCRIPTION

The Pacific Solid Core doorset is a flush-panel door set, typically prehung on high quality steel hinges in a timber or steel frame.

Doorsets are available as single leaf or pair leaf, finished in a variety of facings.

The standard doorset is intended for interior use in dry conditions, however this door set is suitable for exterior use with the right leaf facing.

Solid Core doorsets are suitable for commercial and moderate institutional use where some impact resistance is required.

Pacific Standard Commercial doorsets are supplied in their natural state ready for a paint or varnish finish.

For further information on this product, visit:

<https://www.pacificdoors.co.nz/products/commercial/pacific-solid-core-doorset>

PRODUCT OPTIONS

Leaf Type

Core

Particle Board 30mm

Rails, Stiles

Radiata Pine, butt-joined and stapled

Clashing

Paint Quality doors are unclashed as standard. Veneered doors are clashed in matching timber, thickness 5mm, to vertical edges.

Facings

Medium Density Fibreboard is standard

Pre-easing

2mm

Thickness

This door leaf is available as 38, 40, 42, 45 or 47mm thick. Standard size is 40mm thick. Minimum leaf thickness for steel framed doors is 45 mm.

Leaf Sizes

The solid core door is available for manufacture to any practical size to suit client requirements. Thought should be given to the facings of oversize door leafs so that there is no visible join in the face of the door.

Leaf Facings


The facings listed below are available for the Solid Core door set

- MDF
- Oil Tempered Hardboard
- Hardboard
- Plywood
- Timber Veneers
- Bolection Panels
- Raised Panels
- Decorative Timber Mouldings
- Solid Timber (thickness up to 12mm)
- Metal Sheet, mild or stainless (0.6 - 1.0mm)
- Aluminium Sheet (0.3 - 1.0mm)
- High Pressure Laminate up to 1.5mm thick (eg: Laminex, Formica)
- Fire Rated Formica
- Sheet Vinyl (1.25 - 2mm)
- Acrylic - Sheets up to 1.5mm thick (eg: Acrovyn, Korogard)
- Laminex Decoral

Leaf Edges

Leaf Edges


The leaf edges listed below are available for the Solid Core door set



Note: leaf thickness may affect the availability of extruded profiles.

Meeting Stiles


The meeting stiles listed below are applicable to paired door sets only.



Frame Types & Profiles


Timber Frame

The timber frame profiles listed below are available for the Solid Core door set



Steel Frame

The steel frame profiles listed below are available for the Solid Core door set




Standard frames are three-sided only with no sill. Four-sided frames and/or custom sills may be available on request. For more in depth information on frame profiles and sizes, please see our Installation Instructions.

Vision Panels

Vision panels for the Solid Core door set are available with timber, aluminium or steel bead, and can be of any practical size within the door leaf provided that there is a minimum 150mm perimeter rail as shown below.

Glazing can be of any type to suit your requirement.



Performance

Thermal insulation

This door leaf has a thermal insulation rating (R-value) of 0.368 Km²/W (for a 40 mm thick leaf).

Exterior installation

This door is not tested for water ingress in exterior installations and we make no statement as to its suitability under NZBC E2 "External moisture". All exterior doors should be given as much shelter as possible and be fitted with appropriate flashing systems.

Hardware

There are no hardware limitations for the Solid Core door set, however consideration should always be given to fitness for purpose.

Concealed hinges are not an option on this doorset.