03/11/2026

Data Sheet

Pacific 3UE-X Exterior Security Door

Pacific Doors offers a range of Security door sets that have been named the 'Protector' series.

These door sets are designed with the intention of 'Keeping Out' any intruder on the basis that they may try to attain entry using a variety of methods such as guns, explosives or hand tools. Many of these door sets come with a certified fire rating to provide an additional level of security.

Description

The 3UE-X is intended for commercial premises requiring economical security protection in an access door or an emergency exit door. This door set is a commercial grade exterior security door set resistant to forced entry with hand tools from the outside face.

Product features:

- Single leaf only
- Multipoint locking system
- Suitable for both interior and sheltered exterior use
- Compatible with timber stud and masonry wall
- Security tested to ENV 1627-30:1999 standard
- Explosion tested to EN 13124:2004 standard

Typical applications:

- Factories
- Warehouses
- Retail premises
- Carpark buildings

For further information on this product, visit:
https://www.pacificdoors.co.nz/products/security/security-doors/3ue-x

Public

Product options

Leaf size and wall type

Leaf size
The door set is suitable for both interior and sheltered exterior use.

	Rating	Standard	Description
Burglar Resistance	Class 3	ENV 1627-30	5-minute attack with a range of hand tools
Explosion Resistance	EXR 1	EN13124	3kg TNT at 5 metres

Test results apply to a single door only, with the specification and hardware described. The hinge face of the door is the designated attack face.

The thickness of the 3UE-X door leaf is 47mm with an approximate leaf weight of 26kg/m2.

Wall Type	Fire Resistance Rating (FFR)	Door Application	Max Leaf Height (mm)	Max Leaf Width (mm)
Timber Stud Masonry	N/A	Single	2300	1089

Notes:


1. This door set has a minimum size of 1673h x 792w.

Wall Types
This door set is suitable for installation into a timber or masonry wall of equal security construction as the door type.

Door Leaf Options

Leaf Facings
Both faces consist of galvanised steel sheet bonded to a steel perimeter channel. The core consists of high-density polystyrene.

Leaf Edges
The leaf edges are capped with steel cappings.


Folded Steel/Ali Cap

Public

Meeting Stiles
This door set is not available as a pair.


Frame Types and Profiles

Timber Frame
This door set is only available in a steel frame.

Steel Frame
The leaf is hung in a four-sided frame of 2mm folded steel. The frame sections are mechanically joined at the corners without the need for welded joints.

The frame is fitted with two hinge bolts on the hinge jamb to prevent the removal of the leaf from the frame.

The frame is fitted with a concealed perimeter seal and the leaf can be fitted with a Raven RP26 weather seal along the bottom edge.



Standard frames are three-sided only, with no sill. Four-sided frames and/or custom sills may be available on request. For more in-depth information on frame profiles and sizes, please see our Installation Instructions.

Vision Panel
Vision panels are not currently an option on this door set. Please contact Pacific Doors to discuss your requirements.

Performance

Security Testing
The door set is rated to level 3 of the European standard ENV 1627-30:1999 “Windows, doors, shutters – Burglar resistance”. This testing incorporates a static load test with applied loads of up to 600 kg as well as manual attack for 5 minutes with a range of hand tools.

Explosive Testing
The Pacific 3UE-X is tested to level EXR 1 of “EN 13124:2004 Windows, doors and shutters – Explosion resistance”.

An explosive charge of 3 kg TNT was detonated 5 metres away from the door.

Thermal insulation
This door leaf has a thermal insulation rating (R-value) of 1.333 Km2/W.

Public