



ARDEX DS60 DECOUPLING MAT

Rubber Membrane Tiling Isolation Mat



ARDEX New Zealand Ltd
Ph 0800 2 ARDEX www.ardex.co.nz

AUCKLAND Ph (09) 580 0005 Fax (09) 296 7689
WELLINGTON Ph (04) 568 5949 Fax (04) 568 6376
CHRISTCHURCH Ph (03) 373 6900 Fax (03) 384 9779

ARDEX Australia Pty Ltd
Technical Services Toll Free: 1800 224 070
www.ardexaustralia.com.au

NSW Ph (02) 9851 9100 Fax (02) 9838 7970
QLD Ph (07) 3817 6000 Fax (07) 3881 3188
VIC/TAS Ph (03) 9308 9255 Fax (03) 9308 9332
SA Ph (08) 8268 2511 Fax (08) 8345 3207
WA Ph (08) 9256 8600 Fax (08) 9455 1227



**Invest in the life of
your tiled floor**





Invest in the life of your tiled floor

The ARDEX DS60 Decoupling Mat isolates a tiling system from possible subfloor movement by debonding from the substrate. Over 95% of tile cracking is the result of substrate movement. Protect your flooring from cracking and damage with this unique decoupling system.



SUBFLOOR VERSATILITY

Install hard wearing tile flooring in more situations. ARDEX DS60 can be used to tile over difficult to adhere to surfaces such as bitumen membranes, epoxy and old composite cork or vinyl flooring. A clean, unblemished surface for the adhesive to adhere to is created, simplifying the problem of replacing old flooring.



PERMANENT OR FLOATING SYSTEM

ARDEX DS60 is unique because it can be installed as a permanent or floating system, the latter being ideal for leased or frequently updated spaces such as in shopping malls, hotels and retirement homes. This ensures the cost effective reinstatement of the original floor at the end of the lease period, upon refurbishment or where the floor finish is updated regularly. Tiled areas installed with a floating ARDEX DS60 decoupling system can be removed or replaced with minimal mess, damage, cost or hassle.



NO DELAYS

A water based adhesive that requires no 'flash off' time is used to hold the ARDEX DS60 to the substrate. Tile adhesive can be applied directly after laying the Decoupling Mat and grouting can be completed 24 hours later. The tiled area is able to withstand foot traffic only 48 hours later.



ARDEX Decoupling Mat System




ARDEX DS60 DECOUPLING MAT
40m x 1.4m
x 0.4mm

ARDEX GROUTS
Choose the best option for the type of tile being used.
Eg. ARDEX FG8, ARDEX FSDD or ARDEX MG

ARDEX TILE ADHESIVES
ARDEX polymer based adhesives are best suited to the Decoupling Mat System.
Eg. ARDEX X56, ARDEX X77 and ARDEX X78.

ARDEX AF360 DECOUPLING ADHESIVE
18kg



SIMPLE TO INSTALL

The ARDEX DS60 Decoupling Mat can be installed easily by applying the water soluble paste, ARDEX AF360, to the substrate and laying the mat down straight away. Tile adhesive is applied as per normal practices.



ARDEX DS60 Decoupling Mat has been laid under the tiles in The Centre City Mall in New Plymouth.

ARDEX WATERPROOFING PRODUCTS
ARDEX can supply a range of liquid or sheet waterproofing products to ensure your tiled area remains watertight.

Speak to your ARDEX representative for advice on waterproofing products.



SYSTEMARDEX
PREMIUM PERFORMANCE

■ DOESN'T IMPACT ON TILE HEIGHT

At only 0.4mm thick, ARDEX DS60 doesn't cause height build up issues with doors and floor levels.

■ RELIABLE MATERIALS

Made from ARDEX's Butynol based technology, ARDEX DS60 eliminates the problem of bitumen bleeding through grouts or spreading loads or heat.

■ TECHNICAL SUPPORT

Complete system specifications and recommendations based on SystemARDEX technology

■ COST EFFECTIVE

Comparative to the entire installation cost of a tiling job, ARDEX DS60 is a low cost investment that protects the life of a tiled floor.