

# CONTEGA FIDEN EXO

Pre-compressed joint sealing tape for exterior use that is open to diffusion and resistant to driving rain



## Technical data

Substance		
Material	open-cell polyurethane flexible foam with polymer impregnation	
Attribute	Regulation	Value
Colour		anthracite
MVTR		< 2.5 MNs/g
Fire behaviour	DIN 4102	B1, P-NDS04-1001
Joint permeability	EN 1026	$a < 0,1 \text{ m}^3/[(h \cdot m \cdot (\text{daPa})n]$
Loading group	DIN 18542	BG1
Resistance to driving rain	EN 1027	requirements fulfilled up to 600 Pa
Weather resistance	DIN 18542	passed
Can be plastered/painted over		yes
Compatibility with conventional construction materials	DIN 18542	yes
Application temperature		above +1 °C / 34 °F
Temperature resistance		permanent: -30 °C/-22 °F to +90 °C/194 °F
Storage		1 °C/ 34 °F - 20 °C/68 °F, 12 months, cool and dry

## Area of application

The CONTEGA FIDEN EXO pre-compressed joint sealing tape for exterior use can be used to create joints on building structures in a manner that is open to diffusion and resistant to driving rain.

This particularly weather-resistant tape has a self-adhesive surface on one side for easy installation.

## Forms of delivery

Art. no.	GTIN	Length	Width	Joint	Weight	PU	Container
15547	4026639155474	10 m	10 mm	2-3 mm	0.119 kg	30	1800
15548	4026639155481	10 m	15 mm	2-3 mm	0.206 kg	20	1200
15549	4026639155498	8 m	10 mm	3-6 mm	0.142 kg	30	1800
15550	4026639155504	8 m	15 mm	3-6 mm	0.214 kg	20	1200
15552	4026639155528	5 m	15 mm	5-10 mm	0.219 kg	20	1200
15553	4026639155535	5.6 m	20 mm	5-10 mm	0.289 kg	15	900
15554	4026639155542	4.3 m	15 mm	7-12 mm	0.219 kg	20	1200
15555	4026639155559	4.3 m	20 mm	7-12 mm	0.289 kg	15	900
15556	4026639155566	3.3 m	20 mm	8-15 mm	0.279 kg	15	900
15557	4026639155573	2.6 m	20 mm	10-18 mm	0.341 kg	15	900
1AR00229	4026639202291	10 m	10 mm	2-3 mm	0.119 kg	30	1800
1AR00231	4026639202314	8 m	15 mm	3-6 mm	0.214 kg	20	1200
1AR00232	4026639202321	5.6 m	20 mm	5-10 mm	0.289 kg	15	900

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

### MOLL

**bauökologische Produkte GmbH**  
Rheinalstraße 35 - 43  
D-68723 Schwetzingen  
Fon: +49 (0) 62 02 - 27 82.0  
Fax: +49 (0) 62 02 - 27 82.21  
eMail: info@proclima.de



## Advantages

- ✓ Particularly weather-resistant
- ✓ BG1 quality
- ✓ Resistant to driving rain and open to diffusion
- ✓ RAL quality-tested installation
- ✓ Large range for all standard joint widths

## Substrates

Clean any loose dust and dirt from the joint. The masonry may need to be levelled with a smooth finish (e.g. mortar joints). Clean the sides of the window frames.

Adhesion to frozen surfaces is not possible. The substrate material must be free of water-repellent substances (e.g. grease or silicone). Subsurfaces must be sufficiently dry and have sufficient load-bearing capacity.

Permanent adhesion is achieved on planed and painted wood, hard plastics, hard wood-based panels (chipboard, OSB, plywood panels) and metal.

The best results in terms of structural stability are obtained on high-quality substrates.

It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases.

## General conditions

The tape must be stored in a cool place on the building site when temperatures are above 20 °C. When temperatures are below 8 °C, the tape should ideally be kept above this temperature. Select the tape dimensions and planning of the joint dimension according to the RAL guideline for planning and carrying out the installation of windows and doors.

Allow 1 cm of additional length of the tape for every metre length of the joint (compressed installation). Use butt-joints at corners and longitudinal joints. Ensure the tape remains in place until decompressed by using the self-adhesive surface on a suitable subsurface. Fit the tape with an offset of at least 2 mm inside the edge of the joint for engineering reasons.

To avoid decompression of already-started rolls: fix the ends of the tape with a staple or else wrap an adhesive strip fully around the tape. Store the rolls lying flat. Place a weight on the side of already-started rolls.

Check compatibility before plastering or painting over the tape.

Do not bring the tape into contact with aggressive chemicals or clean it using aggressive chemicals.



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

**MOLL**  
**bauökologische Produkte GmbH**  
Rheinalstraße 35 - 43  
D-68723 Schwetzingen  
Fon: +49 (0) 62 02 - 27 82.0  
Fax: +49 (0) 62 02 - 27 82.21  
eMail: [info@proclima.de](mailto:info@proclima.de)

