

Cabot's Cabothane Oil Based Matt

NZDW0827

Part A	864-94856
---------------	-----------




Description
CABOT'S Cabothane Matt is a clear one-pack polyurethane based varnish for all interior timbers.

Features
<ul style="list-style-type: none"> • One-pack varnish • Clear film • Oil base • Polyurethane base

Benefits
<ul style="list-style-type: none"> • No mixing, apply direct to timber • Enhances natural colour and texture • Suitable to seal CABOT'S Interior Stain • Tough hard wearing

Uses
Use CABOT'S Cabothane Low Sheen on all interior timbers and wood veneers, and as a clear finish over CABOT'S Interior Stain.

Performance Guide			
Weather	For interior use only, not recommended for exterior use.	Salt	Unaffected by splash or spillage
Heat Resistance	Up to 120C. Premature yellowing and embrittlement will occur if subjected to continuous heat.	Water	Good water resistance.
Solvent	Resists alcohol and hydrocarbons.	Abrasion	Good resistance to abrasion.
Acid	Suitable for splash (dilute only)	Alkali	Suitable for splash (dilute only)

Typical Properties																											
Gloss Level	Matt	Thinner	Not Required																								
Colour	Clear	Components	1																								
Number Of Coats	2-3	Toxicity	Lead free. Dry film is non-toxic.																								
V.O.C. Level	483 g/L	Sanding Properties	Very Good																								
Touch Dry	2 Hours																										
Clean Up	 Thinner																										
Clean Up Description	Clean up all rquipment with mineral turpentine																										
Application Method	  Brush Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">42</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">64</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">27</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">8 Hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td style="text-align: center;">15.6</td> </tr> </table>			Solids By Volume	42				Min	Max	Recommended	Wet Film Per Coat (microns)			64	Dry Film Per Coat (microns)			27	Recoat Time (min)	8 Hours	Indefinite		Theoretical Spread Rate (m ² /L)			15.6
Solids By Volume	42																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			64																								
Dry Film Per Coat (microns)			27																								
Recoat Time (min)	8 Hours	Indefinite																									
Theoretical Spread Rate (m ² /L)			15.6																								

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other contaminants. Wash with mineral turpentine if needed to remove wax and grease, allow to dry, and lightly sand dressed surfaces with "00" paper or finer, always in direction of the grain. Dust down thoroughly. Fill nail holes with CABOT'S Wood Tone Putty - do not use a linseed oil putty.
Application Procedure And Equipment	<ul style="list-style-type: none"> Brush, short-nap roller or pad Stir thoroughly before and during use with a broad flat stirrer to maintain a uniform solution. Apply two - three coats with at least 8 hours drying between coats. Brush application, always laying off along the grain. If timber is to be stained, apply one coat of CABOT'S Interior Stain in selected colour, allow at least 12 hours drying then apply two - three coats Cabothane. Sand lightly between coats of Cabothane.

Health And Safety			
MSDS Number	7525	Using Safety Precautions	For detailed information refer to the product label and the current Material Safety Data Sheet available through CABOT'S Sales and Customer Service Offices.
MSDS Link	http://msds.duluxgroup.com/pdf/shess-en-cds-020-00000007525.pdf		
Health Effects	Health Effects: Splashes to eyes will cause irritation. Prolonged contact with liquid is harmful and inhalation of vapour and spray mists may produce respiratory irritation and headaches.	Flammability	This product is flammable.
Protective Equipment	Wear eye protection, protective clothing and gloves.	Storage	Store and use away from sources of heat and ignition.
Disposal	Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.		
In the case of emergency, please call 0800 734 607			

Precautions And Limitations

Do not apply product if temperature is below 10C or is likely to fall below 10C during the drying period.
 Moisture content of timber should be close to equilibrium moisture content, usually 10-15%, but not exceeding 15%, for satisfactory application.
 For interior use only.

Transport And Storage

Pack A	864-94856	Shipment Name	PAINTS, flammable liquid, high flash point.
Size	4 Litre 1 Litre 500ml 250ml	Weight	4.1 Kg 1.1 Kg 600g 300g
Flash Point	43C	UN Number	1263
Dangerous Goods Class	3b	Package Group	III

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118