

Cabot's Exterior Clear Gloss

NZDW0831

Part A	864-82147
---------------	-----------




Description
CABOT's Exterior Clear is a UV resistant, oil based clear gloss finish for exterior timber.

Features
<ul style="list-style-type: none"> ▪ Clear finish ▪ High UV resistance ▪ Mould resistant

Benefits
<ul style="list-style-type: none"> ▪ Highlights timber grain and colour ▪ Good durability

Uses
Use CABOT's Exterior Clear on exterior timber doors, windows, pergolas, fascias and balustrading.

Performance Guide			
Weather	For exterior use.	Salt	Unaffected by splash or spillage
Heat Resistance	Up to 120°C. Premature yellowing and embrittlement will occur if subject to continuous heat.	Water	Good water resistance.
Solvent	Resists alcohol and hydrocarbons.	Abrasion	Good resistance to abrasion.
Acid	N/A	Alkali	N/A

Typical Properties																											
Gloss Level	90 - 100 % at 85 degrees	Thinner	Not required																								
Colour	Clear	Components	1																								
Number Of Coats	3	Toxicity	Lead Free. Dry film is non toxic.																								
V.O.C. Level	418 g/L	Sanding Properties	Good																								
Touch Dry	4 hours																										
Clean Up	 Thinner																										
Clean Up Description	Thoroughly clean all equipment with mineral turpentine																										
Application Method	 Air Spray  Brush																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">46</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">85</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">39</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">12 hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td style="text-align: center;">11.8</td> </tr> </table>			Solids By Volume	46				Min	Max	Recommended	Wet Film Per Coat (microns)			85	Dry Film Per Coat (microns)			39	Recoat Time (min)	12 hours	Indefinite		Theoretical Spread Rate (m ² /L)			11.8
Solids By Volume	46																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			85																								
Dry Film Per Coat (microns)			39																								
Recoat Time (min)	12 hours	Indefinite																									
Theoretical Spread Rate (m ² /L)			11.8																								

Application Guide

Surface Preparation	<ul style="list-style-type: none"> All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other contaminants. Wash with mineral turpentine if needed to remove wax and grease, allow to dry, and lightly sand dressed surfaces with 180-240 grit paper, always in direction of the grain. Remove any sharp edges on the timber by sanding. This will allow an even film build on the surface being coated.
Application Procedure And Equipment	<ul style="list-style-type: none"> Brush or Roller. Stir contents thoroughly before and during use with a broad flat stirrer, to maintain a uniform solution. Apply by brush straight from the can without thinning. Brush along the full length of each board or surface to be coated in direction of the grain. Apply at least 3 liberal coats to the timber allowing 12 hours between coats. Sand lightly between coats. DO NOT OVERSPREAD THE PRODUCT. For best results, all the timber should be coated with at least 1 coat to all surfaces prior to installation, which helps prevent moisture ingress in to the timber. <p>MAINTENANCE - If any breakdown occurs in the coating, repair immediately. Minor degradations will spread quickly, leading to extensive preparation and recoating requirements.</p>

Health And Safety

MSDS Number	14506801	Using Safety Precautions	For detailed information refer to the product label and the current Material Safety Data Sheet available through CABOT'S Sales and Customer Service Offices.
MSDS Link	http://msds.duluxgroup.com/pdf/shess-en-cds-020-000014506801.pdf		
Health Effects	Splashes to eyes will cause irritation. Prolonged contact with liquid is harmful and inhalation of vapour and spray mists may produce respiratory irritation and headaches.	Flammability	This product is flammable.
Protective Equipment	Wear eye protection, protective clothing and gloves.	Storage	Store and use away from sources of heat and ignition.
Disposal	Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.		

In the case of emergency, please call 0800 734 607

Precautions And Limitations

Do not apply product if temperature is below 10C or is likely to fall below 10C during the drying period. Do not apply if rain is likely to fall on the coating during application or drying.
 Moisture content of timber should not exceed equilibrium moisture by more than 15% for satisfactory application.
 For exterior use only.
 Do not apply directly to water repellent pre-treatments containing wax.
 Do not use on walked on areas such as decks. Not suitable for outdoor furniture or weatherboards.

Transport And Storage

Pack A	864-82147	Shipment Name	PAINTS, flammable liquid, high flash point.
Size	500 ml 1 Litre	Weight	560g 1.1 Kg
Flash Point	36C	UN Number	1263
Dangerous Goods Class	3b	Package Group	111

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118