

Cabot's Floor Polish

NZ_DW01861

Part A	918-82162
---------------	-----------




Description
CABOT'S Floor Polish is a protective finish for sealed cork, parquetry and timber floors.

Features
<ul style="list-style-type: none"> ▪ Water based ▪ Quick drying ▪ Good wet-out ▪ Easy to apply

Benefits
<ul style="list-style-type: none"> ▪ Easy clean-up ▪ Low odour ▪ Walk on in 1 hour ▪ Will stick to most surfaces ▪ Simply mop on

Uses
Use CABOT'S Floor Polish periodically when the appearance of the timber floor coating needs rejuvenating (e.g. every 6 months), this will prolong the life of your timber floor coating. Use CABOT'S Floor Polish to coat on any sealed interior surface.

Performance Guide			
Weather	Interior only	Salt	Good
Heat Resistance	Upto 50C	Water	Good splash resistance
Solvent	Fair	Abrasion	Good
Acid	Fair	Alkali	Very poor

Typical Properties																											
Gloss Level	85% at 85 degrees	Thinner	DO NOT THIN																								
Colour	Clear	Components	1																								
Number Of Coats	1 or 2 coats	Toxicity	Lead free. Dry film is non-toxic																								
V.O.C. Level	90 g/L	Meets GBCA VOC Requirement?	N/A																								
Touch Dry	20 minutes																										
Clean Up	 Water																										
Clean Up Description	Thoroughly clean all equipment with water.																										
Application Method	  Brush Roller																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">22</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">18</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">4</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">1 Hour</td> <td style="text-align: center;">Indefinite</td> <td style="text-align: center;">55</td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td style="text-align: center;">55</td> </tr> </table>			Solids By Volume	22				Min	Max	Recommended	Wet Film Per Coat (microns)			18	Dry Film Per Coat (microns)			4	Recoat Time (min)	1 Hour	Indefinite	55	Theoretical Spread Rate (m ² /L)			55
Solids By Volume	22																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			18																								
Dry Film Per Coat (microns)			4																								
Recoat Time (min)	1 Hour	Indefinite	55																								
Theoretical Spread Rate (m ² /L)			55																								

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> PREVIOUSLY COATED SURFACES All surfaces should be thoroughly clean, dry and free from wax, oil, grease and other contaminants.
Application Procedure And Equipment	<ul style="list-style-type: none"> Brush, applicator or short nap roller Do not shake Apply by mop, pad or roller, working in a smooth, even action to avoid aeration

Health And Safety			
MSDS Number	14440201	Using Safety Precautions	For detailed information refer to product label and the current Safety Data Sheet available through CABOT'S Sales and Customer Service Offices
MSDS Link	http://msds.duluxgroup.com/pdf/shess-en-eds-020-000014440201.pdf		
Health Effects	Splashes to eyes will cause irritation. Prolonged contact with liquid is harmful and inhalation of vapour may produce respiratory irritation and headaches.	Flammability	This product is not flammable
Protective Equipment	Wear eye protection, protective clothing and gloves.	Disposal	Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.
In the case of emergency, please call 0800 734 607			

Precautions And Limitations

Do not apply product if temperature is below 10 degrees or above 30 degrees or is likely to reach these temperatures during the drying period. Equally, relative humidity should not exceed 85%.
Check the adhesion on a small area first. On very smooth surface, such as ceramic tiles, adhesion may be poor.

Transport And Storage

Pack A	918-82162	Shipment Name	Not dangerous goods. No special transport requirements
Size 1 Litre	Weight 1.2Kg		
Flash Point	NA	UN Number	NA
Dangerous Goods Class	NA	Package Group	NA

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118