

Cabot's Garden Furniture Oil Water Based

NZDW1586

Part A	847-line
---------------	----------

Description

Cabot's Water Based Garden Furniture Oil is a highly durable, low odour exterior oil. It is designed to provide exceptional durability to garden furniture, BBQ trolleys and benches and lasts longer than traditional garden furniture oils. Water Based Garden Furniture Oil's advanced dual technology allows natural oils to penetrate and nourish the timber, then creates a durable acrylic barrier for a beautiful natural finish.

- Features**
- Advanced Dual Technology
 - UV protection.
 - Water repellent
 - Dirt and mould resistant.
 - Fast recoat

- Benefits**
- Allows natural oils to penetrate and nourish the timber then creates a durable acrylic barrier
 - Blocks out harmful UV rays preventing them from penetrating and damaging the surface while resisting colour fading
 - Penetrates the timber and forms a water repellent barrier aiding protection against mould and minimises cracking and splitting
 - Contains powerful ingredients to resist the growth of wood staining mould while providing excellent dirt and stain resistance.
 - Recoat after only 2 hours.

Uses

Exterior timber projects including garden furniture, BBQ trolleys and benches

Performance Guide

Weather	Excellent	Salt	Good
Heat Resistance	Up to 70 degrees Celcius	Water	Excellent

Typical Properties

Colour	Natural	Components	1																								
Number Of Coats	2	Toxicity	Lead Free																								
Touch Dry	1 hour																										
Clean Up	 Water																										
Application Method	 Brush																										
Application Conditions	<table border="0"> <tr> <td>Solids By Volume</td> <td>15.5</td> <td></td> <td></td> </tr> <tr> <td></td> <td>Min</td> <td>Max</td> <td>Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td>84</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td>13</td> </tr> <tr> <td>Recoat Time (min)</td> <td>2 hours</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td>12</td> </tr> </table>			Solids By Volume	15.5				Min	Max	Recommended	Wet Film Per Coat (microns)			84	Dry Film Per Coat (microns)			13	Recoat Time (min)	2 hours			Theoretical Spread Rate (m²/L)			12
Solids By Volume	15.5																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			84																								
Dry Film Per Coat (microns)			13																								
Recoat Time (min)	2 hours																										
Theoretical Spread Rate (m²/L)			12																								

Application Guide

Surface Preparation	<ul style="list-style-type: none"> Note: Fill holes and imperfections with a suitable timber putty. <p>BARE TIMBER Allow timber to weather for 4-6 weeks. For exterior surfaces clean with Cabot's Deck Clean following label instructions.</p> <p>PREVIOUSLY PAINTED OR VARNISHED TIMBER Remove back to bare timber using a paint stripper, or sanding. For exterior surfaces clean with Cabots Deck Clean following label instructions.</p> <p>PREVIOUSLY STAINED OR OILED TIMBER For exterior surfaces clean with Cabots Deck Clean following label instructions. Test if the surface is ready for coating by sprinkling water on the timber. If the water beads on the surface, repeat the application of Cabots Deck Clean. If water is absorbed into timber, it is ready for coating. For a more transparent look, sand timber back to bare before coating.</p> <p>WEATHERED AND GREYED TIMBER For best results, sand timber back to fresh substrate. Clean with Cabots Deck Clean following label instructions.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> APPLICATION <ol style="list-style-type: none"> Stir thoroughly with a broad flat paddle before and during use. Apply liberally along the length of the timber including exposed edges and end grain, by brush. The initial milky colour helps with even product application, drying to a semi-transparent finish. Apply two coats allowing 2 hours between coats. MAINTENANCE Re-apply as the timber changes colour or when water repellency diminishes due to weathering. Follow surface preparation instructions. Brush, Roller

Health And Safety

MSDS Number	22379	Using Safety Precautions	Keep out of reach of children. Avoid skin and eye contact. Provide adequate ventilation. If using inside keep windows and doors open during application and drying time
MSDS Link	http://msds.duluxgroup.com/pdf/shess-en-cds-020-000000022379.pdf		
Health Effects	<p>22379 For advice contact a Doctor or Poisons Information Centre AUST 131 126, NZ 0800 764 766.</p> <p>SWALLOWED: Give plenty of water to drink. Seek medical advice.</p> <p>EYE: Rinse with plenty of running water. Seek medical advice if irritation occurs.</p> <p>For further information or a copy of the Product Safety Data Sheet telephone Cabots Customer Service Department on AUST 1800 011 006, NZ 0800 222 687.</p> <p>For emergencies phone AUST 1800 033 111, NZ 0800 734 607</p>	Flammability	Non flammable
Storage	Keep out of reach of children	Disposal	Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first

In the case of emergency, please call 0800 734 607

Precautions And Limitations

Do not apply this product in temperatures below 10°C or above 35°C, or when rain or heavy dew is expected during the drying period.
In hot temperatures do not apply in direct sunlight, cool the timber by lightly dampening with water and coat in the shade.

Transport And Storage

Pack A	847-line
Size	Weight
1L	1.2 kg

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118