

**Cabot's Interior Stain Matt**

**NZDW0822**

<b>Part A</b>	859-Line
---------------	----------




<b>Description</b>
Cabot's Interior Stain rejuvenates and transforms the colour of interior timber doors, windows, trim and furniture. It must be over coated with Cabot's Cabothane Clear Oil Based or Cabots Danish Oil to give the protection and durability required on interior timber.

<b>Features</b>
<ul style="list-style-type: none"> <li>• Enhances timber grain</li> <li>• Easy to apply</li> <li>• Clear top coat required</li> </ul>

<b>Benefits</b>
<ul style="list-style-type: none"> <li>• Enriches rather than hides the natural timber grain.</li> <li>• Enriched with oil to nourish and protect timber.</li> <li>• Simply brush on and wipe off.</li> <li>• Topcoat with Cabot's Cabothane Clear Oil Based or Danish Oil to ensure durability and protection.</li> </ul>

<b>Uses</b>
Timber doors, windows, trim and furniture.

<b>Performance Guide</b>			
<b>Weather</b>	For interior use only, not recommended for exterior use.	<b>Salt</b>	Unaffected by splash or spillage.
<b>Heat Resistance</b>	Up to 120C. Prolonged exposure to this temperature will cause yellowing.	<b>Water</b>	Good water resistance when top coated with Cabot's Cabothane Clear Oil Based or Danish Oil.
<b>Solvent</b>	Resists alcohol and hydrocarbons when top coated with Cabothane.	<b>Abrasion</b>	Good abrasion resistance when top coated with Cabot's Cabothane Clear Oil Based.
<b>Acid</b>	N/A	<b>Alkali</b>	Suitable for splash.

Typical Properties																											
<b>Gloss Level</b>	Matt	<b>Thinner</b>	Not required																								
<b>Colour</b>	3 factory packaged + tinted colours	<b>Components</b>	1																								
<b>Number Of Coats</b>	1	<b>Toxicity</b>	Lead free. Dry film is non-toxic.																								
<b>V.O.C. Level</b>	<670g/L	<b>Touch Dry</b>	2 Hours																								
<b>Clean Up</b>	 Thinner																										
<b>Clean Up Description</b>	Thoroughly clean all equipment with mineral turpentine																										
<b>Application Method</b>	  Brush    Roller  Other: Rag																										
<b>Application Conditions</b>	<table border="0" style="width: 100%;"> <tr> <td style="text-align: right;"><b>Solids By Volume</b></td> <td style="text-align: center;">17</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><b>Min</b></td> <td style="text-align: center;"><b>Max</b></td> <td style="text-align: center;"><b>Recommended</b></td> </tr> <tr> <td style="text-align: right;">Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">83</td> </tr> <tr> <td style="text-align: right;">Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">14</td> </tr> <tr> <td style="text-align: right;">Recoat Time (min)</td> <td style="text-align: center;">8 hours</td> <td style="text-align: center;">Indefinite</td> <td></td> </tr> <tr> <td style="text-align: right;">Theoretical Spread Rate (m<sup>2</sup>/L)</td> <td></td> <td></td> <td style="text-align: center;">12</td> </tr> </table>			<b>Solids By Volume</b>	17				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	Wet Film Per Coat (microns)			83	Dry Film Per Coat (microns)			14	Recoat Time (min)	8 hours	Indefinite		Theoretical Spread Rate (m <sup>2</sup> /L)			12
<b>Solids By Volume</b>	17																										
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																								
Wet Film Per Coat (microns)			83																								
Dry Film Per Coat (microns)			14																								
Recoat Time (min)	8 hours	Indefinite																									
Theoretical Spread Rate (m <sup>2</sup> /L)			12																								

Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>▪ Note: Fill nail holes, cracks and other defects with Cabot's Wood Tone Putty after applying the first coat of this product for accurate colour matching. Remove stains, dirt, wax, grease and oil with mineral turpentine. Remove any polish with a suitable floor polish remover.</li> <li><b>BARE TIMBER</b> Sand the surface smooth using 180 - 240 grit sandpaper. Sand only in the direction of the grain. Remove all traces of sanding dust.</li> <li><b>PREVIOUSLY COATED TIMBER</b> Completely remove the previous coating using a paint stripper or by sanding. Remove all traces of sanding dust.</li> <li><b>IMPORTANT</b> The natural colour of the timber will affect the finished colour of the stain. The clear coating used to seal the stain may also have some affect on the final colour. Always test the stain on an off cut or concealed part of the actual job before proceeding.</li> <li><b>STAINING A FLOOR</b> For the best method of staining a floor, please refer to the Cabot's Stain &amp; Varnish range.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>▪ Brush, Roller or Rag</li> <li>▪ Stir thoroughly with a broad flat paddle until pigment is mixed in and colour is uniform. Keep well stirred during use. If using more than one can, mix all cans together into a larger container to ensure colour uniformity. Apply with a good quality brush, roller or lint free rag and work the stain evenly into the grain. Allow to set for 2-10 minutes then rub with a clean soft cloth using a circular motion to remove any excess stain and produce an even coloured surface. The intensity of the colour will depend on porosity of timber and the length of time before the stain is wiped off. Allow 8 hours drying time. Apply Cabot's Cabothane Clear Oil Based or Cabot's Danish Oil as a top coat following label instructions.</li> <li><b>MAINTENANCE</b> Regular inspection of all coated surfaces is recommended.</li> </ul>

Health And Safety			
<b>MSDS Number</b>	14183501	<b>Using Safety Precautions</b>	RISK: Flammable. Irritating to skin. Avoid contact with skin and eyes. Wear suitable protective clothing and gloves. Use only in well ventilated areas. This paint is flammable, so eliminate any sources of ignition. Do not smoke.
<b>MSDS Link</b>	<a href="http://msds.duluxgroup.com/pdf/shess-en-cds-020-000014183501.pdf">http://msds.duluxgroup.com/pdf/shess-en-cds-020-000014183501.pdf</a>		
<b>Health Effects</b>	If poisoning occurs, contact a doctor call 0800 764 766.  SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance.  EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.  SKIN: Wash contaminated skin with plenty of soap and water. If irritation occurs seek medical advice.  For further information or a copy of the Product Safety Data Sheet telephone Cabots Customer Service Department on 0800 222 687.	<b>Flammability</b>	This product is flammable.
<b>Protective Equipment</b>	Wear eye protection, protective clothing and gloves.	<b>Storage</b>	Store and use away from sources of heat and ignition. Keep out of reach of children.
<b>Disposal</b>	Do not contaminate stormwater with product or product washings. Do not pour product down the drain. Unwanted product should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty containers should be left open in a well ventilated area to dry out. When dry, recycle the container via recycling programmes. Disposal of empty paint containers via recycling programmes may differ between local authorities. Check with your local council first.		
<b>In the case of emergency, please call 0800 734 607</b>			

Precautions And Limitations
Do not apply product if temperature is below 10C or is likely to fall below 10C during the drying period. All timings quoted at 25 degrees and 50% humidity.  Only apply to new timber or to timber from which all previous finishes have been removed. Moisture content of timber should be close to equilibrium moisture content, usually 10-15%, but not exceeding 15%, for satisfactory staining.

Transport And Storage			
<b>Pack A</b>	859-Line	<b>Shipment Name</b>	PAINTS, flammable liquid, high flash point.
<b>Size</b>	250ml	<b>Weight</b>	300g
<b>Flash Point</b>	43C	<b>UN Number</b>	1263
<b>Dangerous Goods Class</b>	3b	<b>Package Group</b>	III

**Disclaimer**

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118