

## Cabot's Wood Tone Putty

NZDW0841

Part A	557 LINE
--------	----------

### Description

Previously known as CABOT'S Wood Tone Putty  
 CABOT'S Wood Tone Putty is a coloured non-acrylic water based putty for filling nail holes in interior timbers.

### Features

- Takes every known top-coat
- Takes every known stain
- Colours intermixable
- Sets firmly
- No harmful ingredients

### Benefits

- No restrictions on specifications.
- Water clean up, fast dry.
- Matches natural timber colour, and wide colour choice.
- Does not sink, shrink, crack or fall out.
- Non flammable.



### Uses

Use CABOT'S Wood Tone Putty for filling nail holes, grain, cracks and blemishes in interior timber.

### Performance Guide

<b>Weather</b>	Not formulated for exterior use.	<b>Salt</b>	N/A
<b>Heat Resistance</b>	N/a	<b>Water</b>	N/A
<b>Solvent</b>	N/A	<b>Abrasion</b>	N/A
<b>Acid</b>	N/A	<b>Alkali</b>	N/A

### Typical Properties

<b>Thinner</b>	Water	<b>Colour</b>	4 packaged colours																							
<b>Components</b>	1	<b>Number Of Coats</b>	N/A																							
<b>Toxicity</b>	Lead free.	<b>Shelf Life</b>	Indefinite																							
<b>Touch Dry</b>	30 minutes																									
<b>Clean Up</b>	 Water																									
<b>Clean Up Description</b>	Thoroughly clean all equipment with a damp cloth.																									
<b>Application Method</b>	 Trowel																									
<b>Application Conditions</b>	<table border="0"> <tr> <td><b>Solids By Volume</b></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td></td> <td><b>Min</b></td> <td><b>Max</b></td> <td><b>Recommended</b></td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td>0</td> <td></td> <td>0</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>Recoat Time (min)</td> <td>Vary</td> <td>N/A</td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m<sup>2</sup>/L)</td> <td></td> <td></td> <td></td> </tr> </table>	<b>Solids By Volume</b>	100				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	Wet Film Per Coat (microns)	0		0	Dry Film Per Coat (microns)	0	0	0	Recoat Time (min)	Vary	N/A		Theoretical Spread Rate (m <sup>2</sup> /L)				
<b>Solids By Volume</b>	100																									
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																							
Wet Film Per Coat (microns)	0		0																							
Dry Film Per Coat (microns)	0	0	0																							
Recoat Time (min)	Vary	N/A																								
Theoretical Spread Rate (m <sup>2</sup> /L)																										

Application Guide	
<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other contaminants. Wash with mineral turpentine if needed to remove wax and grease, allow to dry and lightly sand dressed surfaces with "00" paper or finer, always in direction of the grain.</li> </ul>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Apply to nail holes or cracks with a Putty Knife taking care to push the putty into the cavity. Apply in layers not thicker than 4mm, until area is filled. Do not smear into surrounding areas. Wipe off excess with a damp cloth. Allow to dry.</li> <li>Lightly sand across a broad area or along the length of a board. Avoid sanding vigorously or in spots, as this can close the grain and create uneven patches when subsequently stained or varnished.</li> <li>Putty knife</li> </ul>

Health And Safety			
<b>MSDS Number</b>	14272801, 0	<b>Using Safety Precautions</b>	For detailed information refer to product label and the current Material Safety Data Sheet available through CABOT'S Sales and Customer Service Offices
<b>Health Effects</b>	<p>For detailed information refer to product label and the current Material Safety Data Sheet available through Sales and Customer Service Offices.</p> <p>Health Effects: Splashes to eyes will cause irritation. Prolonged contact with liquid is harmful and inhalation of vapour and spray mists may produce respiratory irritation and headaches.</p>	<b>Flammability</b>	This product is non-flammable
<b>Protective Equipment</b>	Personal Protective Equipment: Wear eye protection, protective clothing and gloves, and if spraying wear a respirator with a combined vapour/particulate cartridge.	<b>Disposal</b>	Do not dispose down the drain. Refer to your local council for correct disposal procedures.
<b>In the case of emergency, please call 0800 734 607</b>			

Precautions And Limitations
<p>Do not apply product if temperature is below 10C or is likely to fall below 10C during drying period.</p> <p>Moisture content of timber should be close to equilibrium moisture content, usually 10-15%, but not exceeding 15%, for satisfactory application.</p> <p>For interior use only.</p>

Transport And Storage			
<b>Pack A</b>	557 LINE	<b>Shipment Name</b>	Not dangerous goods.No special transport requirements.
<b>Size</b>	90g	<b>Weight</b>	100g
<b>Flash Point</b>	NA	<b>UN Number</b>	NA
<b>Dangerous Goods Class</b>	NA	<b>Package Group</b>	NA

**Disclaimer**

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (New Zealand) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "Orica" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (New Zealand) Pty Ltd 150 Hutt Park Road NZ ACN 133 404 118