TECHNICAL SPECIFICATION

S'	Y	S	T	Ε	N	١
Ċ.	c	וכ	D	F		

KATT FIXED LADDER SYSTEM

TECHNICAL DATA

MATERIALS

 All componentry and accessories manufactured from high grade structural aluminium with options for powder coating.

DIMENSIONS

- Overall ladder width 605mm
- Distance between stiles 525mm
- Rung diameter 45 x 32mm (profiled)
- Rung spacing 300mm
- Stile extension above landing surface 900mm to 1100mm
- Minimum clearance behind ladder 200mm (vertical position)
- Maximum distance between rest platforms 6.0M

WEIGH.

Ladder body sections – 2.9kg/M (excludes fixing brackets and fixings)
Cage sections – 8.3kg/M

FIXINGS

- Metal fixing M10 bolt set
- Concrete fixing M10 mechanical concrete anchor
- Metal purlin fixing M8 toggle bolt

(Refer instruction manual)

WORKING LOAD LIMIT

Recommended for single person use - 150kg rated.

Industrial rated, suited to high frequency usage.

Support structure integrity, suitability and fixing method to be assessed and determined by a engineer unless it is clear to a competent person prior to installation.

Arresta Vertical Line Fall Arrest System must be only used with the approved fall arrest device and harness system incorporating front chest attachment and energy absorber as per AS/NZS1891.1:2009 (part 4).

COMPLIANCE

Katt Ladder System is designed to comply with requirements of Australian Standards AS1657:2013 and relevant statutory OHS Codes of Practice/

Guidelines.

TESTING

Testing and performance based on requirements of Australian Standards AS1657:2013.

PRODUCT WARRANTY

10 years from date of purchase subject to correct installation, use and maintenance in accordance with manufacturer's specifications and recommendations.

INSPECTION AND MAINTENANCE

Inspection and certification required every 12 months by competent person in accordance with manufacturer's specifications and requirements of Australian Standard AS1657:2013 and AS/NZS 1891.4:2009 Section (9). (Refer instruction manual.)

IMPORTANT NOTE

Failure to supply and/or install proprietary product in accordance with above standards and codes, specifications and instructions voids complete system certification and/or warranty.

IXED LADDER SYSTEN

