



CERTIFICATE OF CONFORMITY

This is to certify that

ModWood Technologies Pty Ltd Wood Plastic Composite Decking and Screening



Product Description

ModWood is a wood-plastic composite (WPCs) product made from a mixture of ground sustainable wood waste and plastic. ModWood products contain no formaldehydes.

Brands:

- ModWood
- ModWood Flame Shield®

ModWood Flame Shield® is a specially formulated ModWood board with a fire-retardant additive included.

Certificate Holder

ModWood Technologies Pty Ltd

ABN: 91 094 868 201
5 Jesica Rd, Campbellfield VIC 3061
Ph: +61 3 9357 8866
W: www.modwood.com.au

Certification Body

CertMark International Pty Ltd

ABN: 80 111 217 568
JAS-ANZ Accreditation No. Z4450210AK
PO Box 321 Tuakau 2121
+64 (09) 951 8246
www.CertMark.org

Complies with the New Zealand Building Code:

1. B1.3.1, B1.3.2, B1.3.3 and B1.3.4
2. B2.3.1 (b) 15 years
3. C3.5 (Relevant to ModWood Flame Shield® only)
4. D1.3.3 (d)
5. E2.3.3 & E2.3.5
6. F2.3.1

Product Purpose or Use

ModWood's Wood Plastic is composite decking and screening for use in residential or commercial projects

Subject to the following Conditions & Limitations:

- a. Must be installed in accordance with the ModWood New Zealand Technical and Installation Guide April 2017.
- b. Only to be installed by a suitably licenced tradesperson.
- c. This certification relates only to the product that is described herein, and has to be read, considered and used as a whole document — it may be considered misleading and will be incomplete to be selective.
- d. Compliance with C3.5 relates only to the ModWood Flame Shield® product.
- e. When installed as decking, the requirements of foundations, subfloor framing, bracing, decking selection, fastenings and fixings are to be installed in accordance with NZS 3604:2011 Section 7.4.
- f. A building consent is required for any deck or balcony that is 1.5m or more above cleared ground level. It should cover construction aspects such as structure, durability, weathertightness at the intersection of deck and building, access (stairs), slip resistance and safety from falling.
- g. Decking must be installed with a 12mm minimum gap between the building cladding and decking for drainage and maintenance as per the requirements of E2/AS1 Paragraph 7.1.1.
- h. The certificate holder must maintain compliance with the conditions set out in Section 15 of the Building (Product Certification) Regulations 2008.


John Thorpe
CertMark International Pty Ltd

25/05/2017

Date of Issue

CMA-CM40210-I01-R00

Certificate Number

- This certificate is issued by an independent certification body accredited by the product certification accreditation body appointed by the Chief Executive of the Ministry of Business, Innovation & Employment (MBIE) under the Building Act 2004. MBIE does not in any way warrant, guarantee, or represent that the building method or product the subject of this certificate conforms to the New Zealand Building Code, nor accept any liability arising out of the use of the building method or product. MBIE disclaims, to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages, and costs arising as a result of the use of the building method(s) or product(s) referred to in this certificate
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the MBIE website, www.mbie.govt.nz
- This certificate may only be reproduced in its entirety.



WWW.JAS-ANZ.ORG/REGISTER