COMMERCIAL TRIMRIB WALL CLADDING (Cladding Change) VERTICAL BUTT FLASHING

DETAIL NO

CTWOO7A

DATE DRAWN

FILE REFERENCE

3/08/10

RI-CTW007A.DWG



2x20 STEEL TEK \$ NEO PAN FIXED


COMPLIANCE WITH E2/AS Omm GAP IF

GAP 5mm MAX TO CLEAR OF PAN OF CLADDING BUILDING WRAP (IF REQUIRED) ROOFING INDUSTRIES TRIMRIB WALL CLADDING REQUIRED -ф TIMBER WALL FRAMING OR SHEET CLADDING ON BUILDING WRAP PLYWOOD, FIBROUS CEMENT LAP SEAL TAPE OR SEALANT

These details are generally in compliance with the NZ Metal Roof & Wall Cladding Code of Practice and in some cases specific details by Roofing Industries!

STEEL GIRTS

- the requirements of the NZ Building Code for the specific project. The building designer is ultimately responsible to ensure that details used meet
- the building designer. Details of the supporting structure are indicative only and are the responsibility of
- Thermal break or cavity battens may be required in some circumstances
- environments including when aluminium is used. Alternative support to galvanised netting should be used in severe coastal Underlay selection and building wrap types are the responsibility of the designer
- applicable to other profiles These details are for Roofing Industries profile/s as nominated and may not be
- This drawing is the copyright of 'Roofing Industries' and can only be copied or reproduced with their permission.
- of Practice www.metalroofer.org.nz & www.roof.co.nz Further information can be obtained from the NZ Metal Roof & Wall Cladding Code Where necessary adjust drawings for purlin battens or cavity battens
- Details are for steel based materials, other substrate may require some changes



©COPYRIGHT DETAIL 2012

