

PACKERS

AIR SEAL

BUILDING WRAP DRESSED INTO OPENING WITH 50mm RETURN TO INSIDE OF FRAME WITH WINDOW FLASHING TAPE FLUSH WITH INSIDE OF FRAME

8mm nom

ALUMINIUM WINDOW

WANZ SUPPORT BAR (0.10.15)

REFER DETAIL BELOW

5 min

10 min

50 min

ROOFING INDUSTRIES SILL FLASHING WITH 10° FALL MIN




GAP 5mm MAX CLEAR OF PAN OF CLADDING

SCREW FIXING

'CAVIBAT' OR SIMILAR

ROOFING INDUSTRIES TRIMRIB

- (1) REFER TO EZAS1 OR WANZ WIS FOR GENERAL WINDOW OPENING, FOR WRAPPING.
- (2) WINDOW PROFILE TO BE SELECTED TO ACHIEVE COVER SHOWN IN DETAILS.
- (3) ARCHITRAVES ARE SHOWN FOR CONSISTENCY ONLY, DETAIL MAY BE USED WITH REBATED LINER.
- (4) WHERE SUPPORT BRACKETS ARE REQUIRED BY THE WINDOW MANUFACTURER TO CARRY THE FRAME AND GLAZING LOADS THEY MUST BE SUPPLIED AS AN INTEGRAL PART OF THE WINDOW MANUFACTURERS RECOMMENDATIONS.
- (5) LAGSE WITH WINDOW MANUFACTURER PRIOR TO INSTALLATION.



NOTE: Sill sealing method for flange end type drainage systems

- Sill flashings stop ended to receive jamb flashings
(Dimensions are indicative only & show minimum lap covers)

NZ METAL ROOF AND WALL CLADDING
CODE OF PRACTICE NZMRM.

DIMENSIONS ARE INDICATIVE ONLY



Roofing Industries
roof.co.nz