JAMB FOR VERTICAL CLADDING. COMMERCIAL RT7 ROLLER DOOR

DETAIL NO

CRT7W090B

DATE DRAWN

28/03/12

FILE REFERENCE

RI-CRT7W090B.DWG

WHERE APPLICABLE (offset for clarity) 4.80 ALUM RIVETS BETWEEN GIRTS ROOFING INDUSTRIES 0.55mm BMI JAMB FLASHING (2 CRESTS)

10mm GAP IF COMPLIANCE WITH E2/AS | REQUIRED

12x65 STEEL TEK & NEO

ROOFING INDUSTRIES RT7

GUIDE RAIL FIXED TO DOOR MULLION

GIRT

GAP 5mm MAX TO CLEAR OF PAN OF CLADDING

BUILDING WRAP (If required)


SCREW FIXING THROUGH PAN

COLUMN

ROLLER SHUTTER DOOR

- These details are generally in compliance with the NZ Metal Roof & Wall Cladding Code of Practice and in some cases specific details by Roofing Industries!
- requirements of the NZ Building Code for the specific project. The building designer is ultimately responsible to ensure that details used meet the
- the building designer. Details of the supporting structure are indicative only and are the responsibility of
- Underlay selection and building wrap types are the responsibility of the designer, Thermal break or cavity battens may be required in some circumstances
- environments including when aluminium is used.

 These details are for Roofing Industries profile/s as nominated and may not be Alternative support to galvanised netting should be used in severe coastal
- applicable to other profiles.
- reproduced with their permission. This drawing is the copyright of 'Roofing Industries' and can only be copied or
- Practice www.metalroofer.org.nz & www.roof.co.nz Further information can be obtained from the NZ Metal Roof \$ Wall Cladding Code of
- Where necessary adjust drawings for purlin battens or cavity battens
- Details are for steel based materials, other substrate may require some changes



©COPYRIGHT DETAIL 2012

