



DETAIL NO

CMRR030C

DATE DRAWN

FILE REFERENCE

RI-CMRR030C.DWG

01/03/12

NOTES

- (1) MINIMUM PITCH 3°
- (2) FOR CAPACITY CALCULATION REFER TO NZMRM CODE OF PRACTICE.
- 4) FOAM CLOSURE STRIP ONLY REQUIRED IN HIGH RISK (3) SNOW STRAPS AND BRACKETS TO BE FITTED AT 600crs IF BIRD OR VERMIN PROOFING IS REQUIRED SITUATIONS OF WIND BLOWN MOISTURE ENTERING OR

25 BOX GUTTER MULTIRIB PROFILE

notine Industries

roof.co.nz

©COPYRIGHT DETAIL 2012

Further information can be obtained from the NZ Metal Roof \$ Wall Cladding Code of reproduced with their permission. This drawing is the copyright of 'Roofing Industries' and can only be copied oi

These details are for Roofing Industries profile/s as nominated and may not be

environments including when aluminium is used.

Alternative support to galvanised netting should be used in severe coastal Underlay selection and building wrap types are the responsibility of the designer,

Thermal break or cavity battens may be required in some circumstances

Details of the supporting structure are indicative only and are the responsibility of

the building designer.

requirements of the NZ Building Code for the specific project.

The building designer is ultimately responsible to ensure that details used meet the

applicable to other profiles.

Practice www.metalroofer.org.nz & www.roof.co.nz

Where necessary adjust drawings for purlin battens or cavity battens

Details are for steel based materials, other substrate may require some changes