PENETRATION SOAKER FLASHING COMMERCIAL MULTIRIB ROOFING

HEM TO EDGE

DETAIL NO.

DATE DRAWN

CMRR019A

01/03/12

FILE REFERENCE

RI-CMRRO I 9A.DWG

These details are generally in compliance with the NZ Metal Roof \$ Wall Cladding Code of Practice and in some cases specific details by 'Roofing Industries'

AS PER NZMR#WCCOP FLOW OR CRICKET FLASHING

NOTES:

- The building designer is ultimately responsible to ensure that details used meet the requirements of the NZ Building Code for the specific project.
- responsibility of the building designer. Details of the supporting structure are indicative only and are the
- circumstances Thermal break or cavity battens may be required in some
- the designer, Underlay selection and building wrap types are the responsibility of

COVER FLASHING

- These details are for Roofing Industries profile/s as nominated and may not be applicable to other profiles. coastal environments including when aluminium is used. Alternative support to galvanised netting should be used in severe
- copied or reproduced with their permission. This drawing is the copyright of 'Roofing Industries' and can only be
- www.roof.co.nz Cladding Code of Practice www.metalroofer.org.nz & Further information can be obtained from the NZ Metal Roof ¢ Wall
- Where necessary adjust drawings for purlin battens or cavity
- Details are for steel based materials, other substrate may require some changes.

NOTES:

- (1) ADDITIONAL SUPPORT FRAMING MAYBE REQUIRED WHEN PENETRATION EXCEEDS 200mm THROUGH ROOF
- (2) REFER TO SECTION 6 OF NZMRM CODE OF PRACTICE FOR CTACHMENT AREA LIMITATION.

©COPYRIGHT DETAIL 2012



